

Remonumentation of Certain Original Corner Points, T. 25 S. R. 2 W.

CHAINS

from which new bearing trees

A hemlock, 9 ins. diam., bears N. $33\frac{1}{2}^{\circ}$ E., $72\frac{1}{2}$ lks. dist., marked $\frac{1}{4}$ S20 BT.

A hemlock, 8 ins. diam., bears S. 83° W., $40\frac{1}{2}$ lks. dist., marked $\frac{1}{4}$ S19 BT.

Deposit the original corner stone alongside the iron post.

The witness cor. of the cor. of secs. 17 18, 19 & 20, monumented with a basalt stone, 16 x 10 x 8 ins., loosely set 5 ins. in the ground, marked WC on the E. face, with 3 notches on the S. and 5 notches on the E. edge, from which the original bearing trees;

A fir, 40 ins. diam., bears N. 25° E., 10 lks. dist., with a healed blaze. (Record distance, 8 lks.)

A fir, 40 ins. diam., bears S. 45° E., 21 lks. dist., with a healed blaze. (Record distance, 19 lks.)

A hemlock, 11 ins. diam., bears N. 53° W., 38 lks. dist., with a healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap marked

T 25 S R 2 W
WC
S 18 | S 17
S 19 | S 20
1962

from which a new bearing tree

A hemlock, 13 ins. diam., bears S. $28\frac{1}{2}^{\circ}$ W., 47 lks. dist., marked X BT.

Deposit the original corner stone alongside the iron post.

The $\frac{1}{4}$ sec. cor. of secs. 17 and 20, perpetuated and recorded by V. W. Hosford, in 1957, monumented with an iron pipe, 36 ins. long, $1\frac{1}{2}$ ins. diam., firmly set 30 ins. in the ground, from which the original bearing trees:

A fir, 32 ins. diam., bears S. 68° W., 11 lks. dist., with a healed blaze.

A down maple, 16 ins. diam., bears S. 51° W., 29 lks. dist., with a healed blaze. (Record bearing distance, N. 69° W., 14 lks.) This tree has slid out of position with no remaining evidence of the stump hole.

and a tree marked by Hosford in 1957

A cedar, 20 ins. diam., bears S. 41° E., 74 lks. dist., with scribe marks T25S R2W $\frac{1}{4}$ S20 RS253 BT visible on unhealed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap marked