

County Surveyor's Record, Douglas County, Oregon
-26-

Remonumentation of Certain Original Corner Points, T. 25 S., R. 2 W.

CHAINS

 $\frac{1}{4}$ S 17
 $\frac{1}{4}$ S 20T 25 S R 2 W
1962

No suitable bearing tree available in Sec. 17.

Deposit iron pipe alongside the iron post.

The $\frac{1}{4}$ sec. cor. of secs. 18 and 19, monumented with a basalt stone, 16 x 8 x 6 ins., firmly set 11 ins. in the ground, marked $\frac{1}{4}$ on the N. face, from which the original bearing trees:

A madrone, 15 ins. diam., bears N. 27° W., 30 $\frac{1}{2}$ lks. dist., with a healed blaze. (Record bearing and distance, N. 22° W., 29 lks.)

A broken hemlock, 20 ins. diam., bears S. 40° E., 13 lks. dist., with a healed blaze. (Record bearing, S. 45° E.)

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 26 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap marked

 $\frac{1}{4}$ S 18
 $\frac{1}{4}$ S 19T 25 S R 2 W
1962

from which new bearing trees

A fir, 6 ins. diam., bears N. 2° E., 33 $\frac{1}{2}$ lks. dist., marked $\frac{1}{4}$ S18 BT.

A hemlock, 15 ins. diam., bears S. 20° E., 35 lks. dist., marked $\frac{1}{4}$ S19 BT.

Deposit the original corner stone alongside the iron post.

The cor. of secs. 7, 8, 17 and 18, perpetuated and recorded by V. W. Hosford in 1957, Monumented with an iron pipe, 36 ins. long, 1 $\frac{1}{2}$ ins. diam., 32 ins. in the ground, from which the original bearing trees:

A hemlock snag, 40 ins. diam., bears N. 18° E., 29 lks. dist., with scribe marks T25S R2W S8 visible on opened blaze. (Record distance, 27 lks.)

A sawed fir stump, 52 ins. diam., bears S. 51° W., 82 lks. dist., with scribe marks W S18 BT visible on opened blaze. (Record distance, 79 lks.)

A broken top fir, 52 ins. diam., bears N. 64° W., 60 lks. dist., with a healed blaze. (Record distance, 56 lks.)

and trees marked by Hosford in 1957

A cedar, 50 ins. diam., bears N. 4° E., 89 lks. dist. with scribe marks S8 253 BT visible on unhealed blaze.

A fir snag, 60 ins. diam., bears S. 54° E., 82 lks. dist., with scribe marks S17 253 BT visible on unhealed blaze.

A sawed hemlock stump, 24 ins. diam., bears S. 32 $\frac{1}{2}$ ° W., 166 lks. dist., with no marks remaining.