

Remonumentation of Certain Original Corner Points, T. 25 S. R. 2 W.

CHAINS

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap marked

T. 25 S. R 2 W
S 7 | S 8
S 18 | S 17
1962

from which new bearing trees

A hemlock, 23 ins. diam., bears N. 28° E., 208 lks. dist., marked T25S R2W BT S8.

A hemlock, 22 ins. diam., bears S. $76\frac{1}{2}^\circ$ E., 172 lks. dist., marked T25S R2W S17 BT.

No suitable bearing trees available in secs. 7 and 18.

Deposit the iron pipe alongside the iron post.

The cor. falls in spring seepage, drain South.

The $\frac{1}{4}$ sec. cor. of secs. 8 and 17, perpetuated and recorded by V. W. Hosford in 1957, monumented with an iron pipe, 36 ins. long, $1\frac{1}{2}$ ins. diam., firmly set 30 ins. in the ground, from which the only remaining original bearing tree:

A hemlock, 17 ins. diam., bears S. 6° W., 20 lks. dist., with scribe mark 4 visible on opened blaze.

and a tree marked by Hosford in 1957

A hemlock, 18 ins. diam., bears N. $72\frac{1}{2}^\circ$ W., $46\frac{1}{2}$ lks. dist., with scribe marks $\frac{1}{4}$ S8 253 BT visible on unhealed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap marked

T $\frac{1}{4}$ S 8
S 17
T 25 S R 2 W
1962

from which new bearing trees

A hemlock, 18 ins. diam., bears N. 21° W., 38 lks. dist., marked $\frac{1}{4}$ S8 BT.

A hemlock, 14 ins. diam., bears S. $1\frac{1}{2}^\circ$ W., 46 lks. dist., marked $\frac{1}{4}$ S17 BT.

Reset the iron pipe alongside the iron post.

The $\frac{1}{4}$ Sec. cor. of secs. 7 and 18, monumented with a basalt stone, 16 x 8 x 8 ins., firmly set 11 ins. in the ground, marked $\frac{1}{4}$ on the N. face, from which the only remaining original bearing tree:

A hemlock, 28 ins. diam., bears S. 16° W., 62 lks. dist., with fragmentary scribe marks visible on partly healed blaze.