

County Surveyor's Record, Douglas County, Oregon

-2-

Dependent Resurvey, Portion of S. Bdy., T. 31 S., R. 5 W.

CHAINS

A fir, 25 ins. diam., bears N. 21° W., 13 lks. dist.,
with a healed blaze. (Record, N. 31° W.)

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the
ground, to solid rock, supported in a mound of stone, 8 ft.
base to top, with brass cap, mkd.

T 31 S R 5 W
S 32 S 33
S 5 S 4
T 32 S
1962

from which

A fir, 13 ins. diam., bears N. $14\frac{1}{2}^{\circ}$ E., 68 lks.
dist., mkd. T31S R5W S33 BT.

A fir, 16 ins. diam., bears S. 38° E., 80 lks.
dist., mkd. T32S R5W S 4 BT.

A fir, 8 ins. diam., bears S. $65\frac{1}{2}^{\circ}$ W., 62 lks.
dist., mkd. T32S R5W S 5 BT.

A fir, 14 ins. diam., bears N. 41° W., 29 lks.
dist., mkd. T31S R5W S32 BT.

S. $88^{\circ} 30'$ W., along the S. bdy of sec. 32, marking and
blazing the true line.

Descent 920 ft. over steep W. slope.

24.30 Ravine, drains N. 85° W.; desc. 205 ft. through ravine.

33.25 Leave ravine, drains S. 75° W., asc. 30 ft. along S. slope.

39.69 Point for the $\frac{1}{4}$ sec. cor. of sec. 5 only, N. bdy. of
T 32 S., R. 5 W., hereinafter described.

40.23 The $\frac{1}{4}$ sec. cor. of sec. 32 only, determined from an
original bearing tree:

A fir, 18 ins. diam., bears S. $68\frac{1}{2}^{\circ}$ E., 38 lks.
dist., mkd. $\frac{1}{4}$ SB on an open blaze.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins.
in the ground, with brass cap mkd.

T 31 S R 5 W
$\frac{1}{4}$ S 32
1962

from which

A fir, 15 ins. diam., bears N. 15° E., 26 lks.
dist., mkd. $\frac{1}{4}$ S32 BT.

A fir, 20 ins. diam., bears N. 57° W., 34 lks.
dist., mkd. $\frac{1}{4}$ S32 BT.

S. $89^{\circ} 22'$ W., beginning new measurement

Ascend 10 ft. along S. slope.

3.00 Spur, slopes S. 10° W; desc. 30 ft. along S. slope.