

Dependent Resurvey, Portion of S. Bdy., T. 31 S., R. 5 W.

## CHAINS

- 19.20 Spur ridge, bears N. 80° E. and S. 80° W.; desc. 305 ft. over NW. slope.
- 33.55 Transmission line, 3-strand, and maintenance road, 15 lks. wide, bears N. 20° E. and S. 20° W.
- 34.70 Creek, 5 lks. wide, course S. 10° W.; asc. 10 ft. over SE. slope.
- 36.05 Road, dirt, 20 lks. wide, bears N. 40° E. and S. 40° W.; thence over level land.
- 39.13 The closing cor. of secs. 5 and 6, T. 32 S., R. 5 W., determined from the original bearing trees:

A fir, 35 ins. diam., bears S. 39° E., 33 lks. dist., with a healed blaze and CC S5 CSBT.

A yew, 9 ins. diam., bears S. 63° W., 39 lks. dist., mkd. CC T32S R5W S6 BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} T\ 31\ S \\ S\ 32 \\ \hline S\ 6\ S\ 5 \\ CC \\ T\ 32\ S\ R\ 5\ W \\ 1962 \end{array}$$

from which

A fir, 6 ins. diam., bears S. 72° W., 58 lks. dist., mkd. T32S R5W S6 CC BT.

Thence over level land.

- 40.87 The cor. of secs. 31 and 32, T. 31 S., R. 5 W., determined from the remains of an original bearing tree:

A down cedar, 12 ins. diam., bears S. 22½° E.; 7 lks. dist., with a burned face, mkd. BT.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} T\ 31\ S\ R\ 5\ W \\ S\ 31\ S\ 32 \\ \hline S\ 6 \\ T\ 32\ S \\ 1962 \end{array}$$

from which

A fir, 6 ins. diam., bears N. 84½° E., 87 lks. dist., mkd. T31S R5W S32 BT.

A fir, 6 ins. diam., bears N. 38½° W., 66 lks. dist., mkd. T31S R5W S31 BT.

Land, mountainous.  
Soil, rocky clay.