

County Surveyor's Record, Douglas County, Oregon

-4-

Dependent Resurvey, Portion of S. Bdy., T. 31 S., R. 5 W.

CHAINS

Timber, fir, hemlock, cedar and madrone; undergrowth, live oak, poison oak, ceanothus, vine maple, and fir reproduction.

Dependent Resurvey of a Portion of the
Subdivisional Lines, T. 32 S., R. 5 W.,
Willamette Meridian, Oregon
(Restoring the 1855 survey by Wells Lake and
George W. Hyde, and the 1901 survey and
retracement by Oscar F. Thiel)

From the cor. of secs. 28, 29, 32 and 33, determined at record bearing and distance from the original bearing trees:

A fir, 28 ins. diam., bears N. 53° E., 27 lks. dist., with a healed blaze. (mkd. by Thiel in 1901.)

A fir snag, 36 ins. diam., bears S. 38° E., 19 lks. dist., mkd. T R on face of partially opened blaze. (mkd. by Thiel in 1901.)

A down and rotted madrone bears S. 20° W., 34 lks. dist., (mkd. by Lake and Hyde in 1855.)

A fir, 36 ins. diam., bears N. 28° W., 38 lks. dist., mkd. T (Mkd. by Thiel in 1901.)

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

T 32 S R 5 W
S 29 S 28
S 32 S 33
1962

from which

A fir, 15 ins. diam., bears S. 49½° E., 118 lks. dist., mkd. T32S R5W S33 BT.

A madrone, 12 ins. diam., bears S. 13° W., 73 lks. dist., mkd. T32S R5W S32 BT.

A fir, 36 ins. diam., bears N. 85° W., 69 lks. dist., mkd. T32S R5W S29 BT.

N. 0° 22' E., bet. secs. 28 and 29, marking and blazing the true line.

Descend 10 ft. over NW. slope, through dense undergrowth.

6.05 Ravine, drains N. 55° E., asc. 68 ft. over SE. slope.

19.935 Point for the S. 1/16 sec. cor. of sec. 29 only.

Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

S 1/16
S 29
1962

from which

A fir, 10 ins. diam., bears S. 34½° W., 106 lks. dist., mkd. S 1/16 S29 BT.

A fir, 7 ins. diam., bears N. 57½° W., 47 lks. dist., mkd. S1/16 S29 BT.