

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines. T. 32 S., R. 5 W.

CHAINS

A yellow pine, 34 ins. diam., bears S. $55\frac{1}{2}^{\circ}$ E., 109 lks. dist., mkd. T32S R5W S28 CS BT.

A fir, 10 ins. diam., bears N. $75\frac{3}{4}^{\circ}$ W., 69 lks. dist., mkd. T32S R5W S20 CS BT.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

T 32 S R 5 W
 S 20 | S 21
 S 29 | S 28
 1962

FD. OK
 9/85
 BY: MAX HULL
 4-29-53
 CS 65/24

from which

A live oak, 6 ins. diam., bears N. 82° E., 110 lks. dist., mkd. T32S R5W S21 BT.

An ash, 8 ins. diam., bears S. 45° E., 143 lks. dist. mkd. T32S R5W S28 BT.

An iron pipe, $1\frac{1}{2}$ ins. diam., 48 ins. long, set 36 ins. in the ground, bears N. 19° W., 46 lks. dist.

Reset the "T" iron alongside the iron post.

Land, mountainous.

Soil, clay, rocky lowm.

Timber, fir, cedar, madrone, white oak, black oak, live oak, yellow pine, willow, alder, chinquapin, and maple; undergrowth, vine maple, salal, arrowwood, poison oak, blackberry and wild rose.

From the cor. of secs. 4, 5, 8, and 9, determined from bearing trees mkd. by O. F. Thiel in 1901.

A fir, 23 ins. diam., bears S. 19° E., 142 lks. dist., with a healed blaze. (Record bearing, S. 21° E.)

A madrone, 25 ins. diam., bears S. 57° W., 75 lks. dist., mkd. T32S R5W S8 BT. (Record bearing, S. 55° W.)

A fir, 35 ins. diam., bears S. 11° W., 40 lks. dist., with chopped and rotted face. (Record bearing, N. 9° W.)

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, to solid rock, supported in a mound of stone, 5 ft., base to top, with brass cap mkd.

T 32 S R 5 W
 S 5 | S 4
 S 8 | S 9
 1962

from which

A fir, 10 ins. diam., bears N. 66° E., 18 lks. dist., mkd. T32S R5W S4 BT.

A fir, 10 ins. diam., bears S. 12° E., 47 lks. dist., mkd. T32S R5W S9 BT.