

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines. T. 32 S., R. 5 W.

CHAINS	
	<p>A fir, 6 ins. diam., bears S. 43° W., 36 lks. dist., mkd. T32S R5W S8 BT.</p> <p>A fir, 14 ins. diam., bears N. $13\frac{1}{2}^{\circ}$ W., 107 lks. dist., mkd. T32S R5W S5 BT.</p> <p>N. 0° 53' W., bet. secs. 4 and 5.</p> <p>Ascend 235 ft. along E. slope, changing to SE. slope.</p>
16.15	Ridge, bears N. 30° E., and S. 30° W.; desc. 25 ft. over NW. slope.
20.22	<p>Point for the S $\frac{1}{16}$ sec. cor. of secs. 4 and 5.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S $\frac{1}{16}$ S 5 S 4 1962</p> <p>from which</p> <p>A cedar, 10 ins. diam., bears N. 17° E., 31 lks. dist., mkd. S $\frac{1}{16}$ S4 BT.</p> <p>A fir, 36 ins. diam., bears S. 35° W., 80 lks. dist., mkd. S $\frac{1}{16}$ S5 BT.</p> <p>Descent 30 ft. over NW. slope.</p>
21.65	Dirt road, 20 lks. wide, bears N. 30° E. and S. 30° W.
24.85	Creek, 2 lks. wide, course S. 25° W.; asc. 60 ft. over SE. slope.
29.85	Spur, slopes S. 70° E.; asc. 10 ft. along E. slope.
35.00	Creek, 1 lk. wide, course S. 60° E.; asc. 80 ft. over SE. slope.
40.44	<p>The $\frac{1}{4}$ sec. cor. of secs. 4 and 5, determined from the remains of an original bearing tree:</p> <p>A fir snag, 7 ins. diam., bears N. $88\frac{1}{2}^{\circ}$ W., 18 lks. dist., mkd. $\frac{1}{4}$ S5 BT.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 32 S R 5 W $\frac{1}{4}$ S 5 S 4 1962</p> <p>from which</p> <p>A fir, 17 ins. diam., bears N. 18° E., $88\frac{1}{2}$ lks. dist., mkd. $\frac{1}{4}$ S4 BT.</p> <p>A fir, 22 ins. diam., bears N. 65° W., 84 lks. dist., mkd. $\frac{1}{4}$ S5 BT.</p>