

County Surveyor's Record, Douglas County, Oregon

-8-

Dependent Resurvey, Subdivisional Lines, T. 32 S., R. 5 W.

CHAINS

N. 2° 10' E., beginning new measurement.

Ascend 240 ft. over SE. slope.

20.26 Point for the N 1/16 sec. cor. of secs. 4 and 5.

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, to solid rock, and in a mound of stone, 5 ft., base to top, with brass cap mkd.

N 1/16
S 5 | S 4
1962

from which

A fir, 40 ins. diam., bears N. 88° E., 195 lks. dist., mkd. N 1/16 S4 BT.

A fir, 17 ins. diam., bears N. 57° W., 84 lks. dist., mkd. N 1/16 S5 BT.

Ascend 5 ft. over SE slope.

20.75 Ridge, bears N. 45° E., and S. 45° W.; desc. 55 ft. over broken NW. slope.

38.59 The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Twp.

Land, mountainous.

Soil, rocky clay, with out-croppings and bluffs on N. ¼ mile. Timber, fir, hemlock, cedar, live oak, undergrowth, fir, reproduction, poison oak, salal, and arrowwood.

From the cor. of secs. 28, 29, 32 and 33.

S. 89° 39' W., bet. secs. 29 and 32.

Descend 43 ft. over NW. slope.

2.75 Ravine, drains N. 45° E.; asc. 137 ft. over SE. slope.

12.60 Spur, slopes N. 45° E.; asc. 315 ft. over NE. slope.

22.40 Ridge, bears N. 15° W. and S. 15° E.; desc. 445 ft. over SW. slope.

39.96 Point for the ¼ sec. cor. of secs. 29 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

T 32 S R 5 W
¼ S 29
¼ S 32
1962

from which

A fir, 14 ins. diam., bears N. 57½° E., 26 lks. dist., mkd. ¼ S29 BT.

A madrone, 8 ins. diam., bears S. 4° E., 45 lks. dist., mkd. ¼ S32 BT.

From this point an iron pipe, ¾ ins. diam., firmly set, protruding 4 ins. above ground, bears S. 17½° W., 37 lks. dist.