

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 32 S., R. 5 W.

## CHAINS

From this same point, the  $\frac{1}{4}$  sec. cor. of secs. 19 and 20 bears N.  $0^{\circ} 58' E.$ , 40.10 chs. dist., determined from bearing trees recorded by the County Surveyor (Briggs) in 1900.

A down fir, bears N.  $62\frac{1}{2}^{\circ} E.$ , 39 lks. dist., mkd.  $\frac{1}{4}$  S BT.

A black oak, 33 ins. diam., bears S.  $29^{\circ} W.$ , 48 lks. dist., mkd. S BT.

At the corner point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 26 ins. in the ground, with brass cap mkd.

T 32 S R 5 W  
 $\frac{1}{4}$   
 S 19 | S 20  
 1962

FO OK  
 9/85  
 BY MAX HULL  
 M 99-33  
 CS 63/24

from which

A fir, 15 ins. diam., bears S.  $84\frac{1}{2}^{\circ} E.$ , 181 lks. dist., mkd.  $\frac{1}{4}$  S20 BT.

A yellow pine, 12 ins. diam., bears S.  $79\frac{1}{2}^{\circ} W.$ , 89 lks. dist., mkd.  $\frac{1}{4}$  S19 BT.

From the same point the  $\frac{1}{4}$  sec. cor. of secs. 19 and 30, determined by a tie to the original witness corner, bears S.  $89^{\circ} 39' W.$ , 40.02 chains distant.

At the corner point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 26 ins. in the ground, with brass cap mkd.

T 32 S R 5 W  
 $\frac{1}{4}$  S 19  
 $\frac{1}{4}$  S 30  
 1962

FO. OK  
 9/85  
 BY MAX HULL  
 M 99-33  
 CS 63/24

from which

A fir, 18 ins. diam., bears N.  $27\frac{1}{2}^{\circ} E.$ , 114 lks. dist., mkd.  $\frac{1}{4}$  S19 BT.

A cottonwood, 35 ins. diam., bears S.  $52^{\circ} W.$ , 199 lks. dist., mkd.  $\frac{1}{4}$  S30 BT.

An ash, 27 ins. diam., bears S.  $75\frac{1}{2}^{\circ} E.$ , 24 lks. dist., mkd.  $\frac{1}{4}$  S CS BT.

From the  $\frac{1}{4}$  sec. cor. of sec. 19 and 30, the original witness corner bears N.  $89^{\circ} 50' E.$ , 0.75 chs. dist., determined from the original bearing trees:

An ash, 24 ins. diam., bears N.  $25^{\circ} E.$ , 33 lks. dist., with a rotted face.

A white oak, 36 ins. diam., bears S.  $2^{\circ} W.$ , 67 lks. dist., with a healed blaze.

This witness corner now becomes a witness point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 26 ins. in the ground, with brass cap mkd.