

County Surveyor's Record, Douglas County, Oregon

-14-

Dependent Resurvey, Subdivisional Lines, T. 32 S., R. 5 W.

CHAINS

Timber, ash, cottonwood, alder, and maple; undergrowth, arrow-wood, live oak, hazel, willow, blackberry and wild rose.

From the cor. of secs. 4, 5, 8 and 9.

N. 88° 48' W., bet. secs. 5 and 8.

Ascend 260 ft. over steep E. slope.

- 5.60 Ridge, bears N. 10° E., and S.; desc. 720 ft. over steep W. slope.
- 15.60 Dirt road, 20 lks. wide, bears N. 30° E. and S. 30° W.
- 23.70 Creek, 3 lks. wide, course S. 45° W.; asc. 120 ft. over SE. slope.
- 28.90 Spur, slopes S.; desc. 10 ft. over SW. slope.
- 30.75 Gully, drains S. 15° E.; asc. 55 ft. over E. slope.
- 34.50 Spur, slopes S.; desc. 45 ft. over SW. slope.
- 38.25 Head of draw, drains S.; asc. 10 ft. over SE. slope.
- 38.39 The $\frac{1}{4}$ sec. cor. of secs. 5 and 8, determined from the original bearing trees:
- A fir, 8 ins. diam., bears N. 17° W., 27 lks. dist.,
mkd. BT.
- A fir, 13 ins. diam., bears S. 49° W., 19 lks. dist.,
mkd. $\frac{1}{4}$ S8 BT.
- At the corner point
- Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone, 5 ft., base to top, with brass cap mkd.
- T 32 S R 5 W
 $\frac{1}{4}$ $\frac{S}{S}$ $\frac{5}{8}$
1962
- from which
- A fir, 10 ins. diam., bears N. $1\frac{1}{2}$ ° W., 67 lks. dist.,
mkd. $\frac{1}{4}$ S5 BT.
- A fir, 20 ins. diam., bears S. $37\frac{1}{2}$ ° W., $63\frac{1}{2}$ lks. dist.,
mkd. $\frac{1}{4}$ S8 BT.
-
- S. 89° 34' W., beginning new measurement.
- Ascend 130 ft. over SE. slope.
- 4.25 Spur, slopes S. 30° W.; desc. 220 ft. over SW. slope.
- 11.75 Spur, slopes S. 35° W.; desc. 250 ft. along broken S. slope.
- 24.25 Spur, slopes S. 65° W.; desc. 65 ft. over NW. slope.
- 27.25 Gully, drains S. 75° W.; asc. 20 ft. over SE. slope.
- 30.30 Spur, slopes S. 35° W.; desc. 110 ft. over SW. slope.
- 40.07 The cor. of secs 5, 6, 7 and 8, determined from the remains of the original bearing trees: