

County Surveyor's Record, Douglas County, Oregon
-15-

Dependent Resurvey, Subdivisional Lines, T. 32 S., R. 5 W.

CHAINS

- A sawed fir stump, 40 ins. diam., bears N. 71° E., 33 lks. dist., with a rotted face.
- A fir snag, 40 ins. diam., bears S. 20° W., 60 lks. dist., with a burned blaze.
- A fir snag, 38 ins. diam., bears N. 41½° W., 32 lks. dist., mkd. T32S R5W S6 on exposed face of burned face.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.

T 32 S R 5 W
S 6 S 5
S 7 S 8
1962

from which

- A chinquapin, 6 ins. diam., bears N. 65° E., 35 lks. dist., mkd. T32S R5W S5 BT.
- A cedar, 6 ins. diam., bears S. 9° E., 55 lks. dist., mkd. T32S R5W S8 BT.
- A cedar, 6 ins. diam., bears S. 14° W., 96 lks. dist., mkd. T32S R5W S7 BT.
- A fir, 6 ins. diam., bears N. 65° W., 45 lks. dist., mkd. T32S R5W S6 BT.

Land, mountainous.

Soil, rock clay.

Timber, fir, hemlock, cedar, live oak and chinquapin, undergrowth, fir reproduction, ceanothus, vine maple, yew, blackberry, salal and poison oak.

N. 0° 50' W., bet. secs. 5 and 6.

Ascend 15 ft. over SW. slope.

- 4.50 Spur, slopes S. 80° W., desc. 35 ft. over NW. slope.
- 8.00 Gully, drains W.; asc. 15 ft. over SW. slope.
- 13.75 Spur, slopes W.; desc. 25 ft. over NW. slope.
- 14.50 Gully, drains S. 85° W.; asc. 66 ft. over SW. slope.
- 21.00 Spur, slopes W.; desc. 55 ft. over N. slope.
- 24.50 Gully, drains N. 50° W.; asc. 80 ft. over SW. slope.
- 30.00 Spur, slopes S. 80° W., desc. 75 ft. over NW. slope.
- 35.50 Gully, drains S. 85° W.; asc. 35 ft. over SW. slope.
- 38.00 Spur, slopes W.; desc. 25 ft. over NW. slope.
- 40.09 The ¼ sec. cor. of secs. 5 and 6, determined from the remains of the original bearing trees:

A sawed cedar stump, 30 ins. diam., bears S. 41° E., 37 lks. dist., with a rotted face. (Record, S. 42° E.)