

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 32 S., R. 5 W.

## CHAINS

A cedar, 32 ins. diam., bears N. 19° W., 51 lks. dist.,  
with an open and chopped face. (Record N. 18° W.)

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 28 ins.  
in the ground, with brass cap mkd.

T 32 S R 5 W  
          ½  
          S 6 | S 5  
          1962

from which

A fir, 6 ins. diam., bears S. 88° E., 38½ lks. dist.,  
mkd. ¼ S5 BT.

A fir, 10 ins. diam., bears N. 78° W., 54 lks. dist.,  
mkd. ¼ S6 BT.

N. 1° 04' E., beginning new measurement.

Descend 3 ft. over NW. slope.

- 0.25 Gully, drains S. 85° W.; asc. 20 ft. over S. slope.
- 2.20 Spur, slopes S. 75° W.; desc. 15 ft. over NW. slope.
- 10.75 Spur, slopes S. 85° W.; desc. 25 ft. over NW. slope.
- 12.50 Gully, drains S. 85° W.; asc. 35 ft. over SE. slope.
- 20.50 Transmission line, bears N. 20° E. and S. 20° W.; also  
maintenance road, 15 lks. wide, bears N. 20° E. and  
S. 20° W.
- 21.00 Spur, slopes S. 70° W.; desc. 30 ft. over NW. slope.
- 33.50 Creek, 5 lks. wide, course S. 55° W.; asc. 25 ft. over SE.  
slope changing to S. slope.
- 34.50 Dirt road, 20 lks. wide, bears N. 60° E.; and S. 60° W.
- 36.83 The closing cor. of secs. 5 and 6.

The cor. of secs. 31 and 32, S. Bdy. of T. 31 S., R. 5 W.,  
bears S. 89° 22' W., 174 chs. dist.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock and cedar; undergrowth, poison oak, vine  
maple, ceanothus, salal, fir reproduction, alder and  
blackberry.

To complete the survey of sec. 5, I return to the ¼ sec. cor.  
of sec 32, only, S. bdy. of T. 31 S., R. 5 W., and run

N. 88° 30' E., along the S. bdy. of sec. 32.

- 0.54 Point for the S. ¼ sec. cor. of sec. 5, only, at mid-point,  
longitudinally, on the N. bdy. of sec. 5.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the  
ground, and in a mound of stone, 4 ft. base to top, with  
brass cap mkd.