

Dependent Resurvey, Subdivisional Lines, T. 32 S., R. 5 W.

CHAINS

$$\frac{1}{4} S 5$$

$$T 32 S R 5 W$$

$$1962$$

from which

A cedar, 12 ins. diam., bears S. $15\frac{1}{2}^{\circ}$ E., 35 lks. dist.,
mkd. $\frac{1}{4}$ S5 BT.

A fir, 10 ins. diam., bears S. 88° W., 23 lks. dist.,
mkd. $\frac{1}{4}$ S5 BT.

Subdivision of Section 29, T. 32 S., R. 5 W.

The following subdivision of sections was executed in conformity with legal surveying practice. The record of true line notes, only, is set forth in the following field notes.

From the $\frac{1}{4}$ sec. cor. of secs. 29 and 32.

N. $0^{\circ} 01'$ E., along the N. and S. center line of sec. 29, marking and blazing true line.

Ascend 132 ft. over SW. slope, through heavy timber and light undergrowth.

7.50 Ridge, bears N. 80° W. and S. 80° E.; desc. 305 ft. over broken N. slope.

12.90 Enter heavy timber, edge bears E. and W.

16.35 Ravine, drains N. 45° W.; desc. 100 ft. over NW. slope.

20.09 Point for the center S $1/16$ sec. cor. of sec. 29.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins in the ground, with brass cap mkd.

$$S \frac{1}{16} \left| \begin{array}{c} C \\ S 29 \\ C \end{array} \right.$$

$$1962$$

from which

A hemlock, 6 ins. diam., bears N. 13° E., 11 lks. dist.,
mkd. CS $1/16$ S29 BT.

A hemlock, 8 ins. diam., bears S. $9\frac{1}{4}^{\circ}$ W., 28 lks. dist.,
mkd. CS $1/16$ S29 BT.

Descend 157 ft. over NW. slope.

28.75 Creek, 1 lk. wide, course N. 25° E.; desc. 147 ft. over NW. slope.

37.45 Creek, 2 lks. wide, course N. 45° E.; asc. 25 ft. over SE. slope.

40.18 Point for the center $\frac{1}{4}$ sec. cor. of sec. 29, at intersection with the E. and W. center line.