

County Surveyor's Record, Douglas County, Oregon

-18-

Dependent Resurvey, Subdivisional Lines, T. 32 S., R. 5 W.

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

C $\frac{1}{4}$
S 29
1962

from which

A fir, 4 ins. diam., bears N. $42\frac{1}{4}^\circ$ W., 21 lks. dist., mkd. XBT.

A fir, 37 ins. diam., bears S. 31° E., 47 lks. dist., mks. C $\frac{1}{4}$ S29 BT.

Descend 170 ft. over N. slope.

- 47.50 Dirt road, 15 lks. wide, bears E. and W.
- 55.20 Irrigation ditch, 3 lks. wide, course W.
- 63.25 Irrigation ditch, 5 lks. wide, course W.
- 72.00 U. S. Highway No. 99, 70 lks. wide, bears N. 80° E. and S. 80° W.
- 80.18 The $\frac{1}{4}$ sec. cor. of sec. 20 and 29.

From the $\frac{1}{4}$ sec. cor. of secs. 28 and 29.

N. $89^\circ 48'$ W., along the E. and W. center line of sec. 29.

Ascend 257 ft. over E. slope, through logged area and dense brush.

- 8.25 Ridge, bears N. 25° E., and S. 25° W.; desc. 429 ft. over NW. slope.
- 20.50 Dirt road, 15 lks. wide, bears N. 20° E., and S. 20° E.
- 38.15 Creek, 1 lk. wide, course N.; asc. 56 ft. over SE. slope.
- 40.29 The center $\frac{1}{4}$ sec. cor. of sec. 29.
- Ascend 16 ft. over SE. slope.
- 41.60 Spur, slopes N. 40° E.; desc. 33 ft. over NW. slope.
- 45.75 Bottom of descent, edge bears NW. and SE. asc. 206 ft. over NE. slope.
- 56.50 Spur, slopes N.; desc. 53 ft. over NW. slope.
- 60.19 Point for the center W $1/16$ sec. cor. of sec. 29.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

C $\frac{W 1/16}{S 29}$ C
1962

from which

A fir, 6 ins. diam., bears N. 11° W., 29 lks. dist., mkd. CW $1/16$ S29 BT.

Pd. OK
 9/85
 BY: MAX HULL
 MS-33
 CS 63/24
 FD. B.C. 8-90-7110-66