

County Surveyor's Record, Douglas County, Oregon

-19-

Subdivision of Section 29, T. 32 S., R. 5 W.

CHAINS

A fir, 18 ins. diam., bears S. $76\frac{1}{2}^{\circ}$ W., 11 lks. dist.,
mkd. CW 1/16 S29 BT.

Descend 50 ft. over N. slope.

61.50 Gully, drains N.; asc. 120 ft. over NE. slope.

65.45 Spur, slopes N. 10° W.; desc. 365 ft. over NW. slope.

73.50 Dirt road, 15 lks. wide, bears N. 50° E. and S. 50° W.

80;05 The $\frac{1}{4}$ sec. cor. of secs. 29 and 30.

From the S 1/16 sec. cor. of sec. 29 only.

S. $89^{\circ} 57'$ W., along the E. and W. center line of the SE $\frac{1}{4}$
of sec. 29.

Ascend 444 ft. over E. slope, changing to SE. slope.

21.20 Ridge, bears N. 40° E. and S. 40° W.; desc. 608 ft. over NW. slope.

40.12 The center S 1/16 sec. cor. of sec. 29.

From the W 1/16 sec. cor. of secs. 29 and 32.

N. $0^{\circ} 09'$ E., along the N. and S. center line of the SW $\frac{1}{4}$
of sec. 29.

Descend 85 ft. over NW. slope.

8.90 Ravine, drains S. 80° W.; asc. 238 ft. over SE. slope.

16.50 Spur, slopes SW.; desc. 142 ft. over NW. slope.

21.00 Bottom of descent, slopes W.; asc. 100 ft. over SW. slope.

31.70 Ridge, bears N. and S. 20° E.; thence along ridge.

34.80 Leave ridge, bears N. 25° W. and S.; desc. 134 ft. over N. slope.

40.38 The center W 1/16 sec. cor. of sec. 29.

Subdivision of Section 5, T. 32 S., R. 5 W.

From the $\frac{1}{4}$ sec. cor. of secs. 5 and 8.

N. $0^{\circ} 15'$ W., along the N. and S. center line of sec. 5,
marking and blazing the true line.

Ascend 675 ft. over steep S. slope.

20.00 Ridge, bears N. 45° E. and S. 45° W.; desc. 35 ft. along W. slope.

29.00 Spur, slopes N. 70° W.; desc. 305 ft. over steep N. slope.

39.61 Point for the center $\frac{1}{4}$ sec. cor. of sec. 5, at intersection
with the E. and W. center line.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins.
in the ground, and in a mound of stone, 4 ft. base to top,
with brass cap mkd.