

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Line bet. Secs. 3 and 4, T. 23 S., R. 4 W..

CHAINS

dist., mkd. S 1/16 S4 BT.

Descend 4 ft. over N. slope.

20.30 Creek, 2 lks. wide, course W.; asc. 155 ft. over S. slope, changing to SE. slope.

22.80 Dirt road, 20 lks. wide, bears NE. curving to E., and SW. curving to W.

32.50 Leave timber and undergrowth, edge bears E. and W., enter open prairie.

32.90 Dirt road, 15 lks. wide, bears E. and W.

39.96 Point for the  $\frac{1}{4}$  sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap marked
$$\begin{array}{c} \frac{1}{4} \\ \text{S } 4 \text{ | S } 3 \\ \text{T } 23 \text{ S | R } 4 \text{ W} \\ 1963 \end{array}$$

from which

A cedar, 10 ins. diam., bears N.  $65\frac{1}{4}^{\circ}$  E., 620 lks. dist., mkd.  $\frac{1}{4}$  S3 BT.A fir, 7 ins. diam., bears S.  $27\frac{1}{2}^{\circ}$  W., 531 lks. dist., mkd.  $\frac{1}{4}$  S4 BT.

Ascend 75 ft. over SE. slope.

58.30 Top of ascent, slopes E.; desc. 15 ft. over N. slope.

58.75 Dirt road, 20 lks. wide, bears NW. and SE.; enter scattering timber and moderate undergrowth, along road.

59.60 Woven wire fence, bears E. and W.

59.94 Point for the N 1/16 sec. cor. of secs. 3 and 4.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 22 ins. in the ground, with brass cap marked
$$\begin{array}{c} \text{N } 1/16 \\ \text{S } 4 \text{ | S } 3 \\ \text{T } 23 \text{ S | R } 4 \text{ W} \\ 1963 \end{array}$$

from which

A fir, 7 ins. diam., bears N.  $52\frac{1}{4}^{\circ}$  E., 147 lks. dist., mkd. N 1/16 S3 BT.A fir, 16 ins. diam., bears S.  $60^{\circ}$  W., 259 lks. dist., mkd. N 1/16 S4 BT.

Descend 15 ft. over NE. slope.

65.00 Small draw, drains E.; asc. 30 ft. over SE. slope.

70.75 Spur, slopes E.; desc. 90 ft. over N. slope.