

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Line bet. Secs. 3 and 4, T. 23 S., R. 4 W.

CHAINS

76.90

Draw, drains E.; asc. 10 ft. along E. slope.

79.92

The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., perpetuated by Wilford N. Haines, Professional Land Surveyor, in June, 1961, with an iron pipe, 3/4 in. diam., protruding 10 ins. above ground, and with a 3/4 in. "T" iron, protruding 8 ins. above the ground, with a brass disc, 3/4 in. diam., on top, mkd. Wilford N. Haines Drain Ore. 239 Survey Point, from which the remains of the original bearing trees:

A rotted fir stump, 25 ins. diam., bears N. 40° E., 38 lks. dist., with no marks remaining.

A fir stump hole, bears N. 50° W., 12 lks. dist.

and trees marked by Haines in 1961:

A cedar, 15 ins. diam., bears N. 89° E., 39 lks. dist., mkd. T22S R4W S34 BT, on open blaze.

A cedar, 17 ins. diam., bears N. 14½° W., 47 lks. dist., mkd. T22S R4W S33 BT, on open blaze.

and a tree marked by persons unknown:

A cedar, 25 ins. diam., bears S. 66 3/4° W., 20 lks. dist., mkd. with partial scribe marks on nearly healed blaze, and mkd. 363, in the bar, by Haines.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap marked

T	22	S	R	4	W
	S	33		S	34
	S	4		S	3
	T	23		S	

*Ed 6/90
M110-30*

from which new bearing trees:

A maple, 17 ins. diam., bears S. 11° E., 94 lks. dist., mkd. T23S R4W S3 BT.

A fir, 8 ins. diam., bears S. 9° W., 45 lks. dist., mkd. T23S R4W S4 BT.

Deposit local corner material beside the iron post.

Land, rolling hills.

Soil, rocky clay loam.

Timber, fir, cedar, maple, madrone, myrtle, oak, and alder; undergrowth, young timber, hazel, ceanothus, arrowwood, huckleberry, salal, Oregon grape, poison oak, vines and ferns.

The following field notes describe the remonumentation of certain original corner points of Township 23 South, Range 4 West, of the Willamette Meridian, Oregon as provided for in the General Special Instructions, Group No. 350 Oregon, dated May 3, 1957, "Investigation of Collateral or Physical Evidence of Corner Positions and Accessories Followed by Remonumentation of Corner Points, With New Accessories When Needed".