

County Surveyor's Record, Douglas County, Oregon

Remonumentation, Original Corner Points, T. 23 S., R. 4 W.

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

$$\begin{array}{c} S \ 30\frac{1}{4}S \ 29 \\ T \ 23 \ S \ | \ R \ 4 \ W \\ 1963 \end{array}$$

from which new bearing trees:

A sawed fir stump, 34 ins. diam., bears N. 72° E., 96 lks. dist., mkd. $\frac{1}{4}$ S29 BT.

A sawed fir stump, 48 ins. diam., bears N. $31\frac{1}{2}^{\circ}$ W., 101 lks. dist., mkd. $\frac{1}{4}$ S30 BT.

The corner is situated at the intersection of barbed wire fences which bear N., S., and W., in old logged and burned area.

The $\frac{1}{4}$ sec. cor. of secs. 20 and 29, determined at record distance from the remains of the original bearing trees:

A fir stump hole, bears N. 44° W., 22 lks. dist., with no marks remaining. (Record bearing, N. 49° W.)

A burned fir stump, 20 ins. diam., bears S. 25° W., 6 lks. dist., with no marks remaining. (Record bearing, S. 22° W.)

and a bearing tree not of record:

A fir snag, 28 ins. diam., bears S. 61° E. 21 lks. dist., mkd. $\frac{1}{4}$ on open blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \ S \ 20 \\ \quad \ S \ 29 \\ T \ 23 \ S \ R \ 4 \ W \\ 1963 \end{array}$$

from which new bearing trees:

A sawed fir stump, 48 ins. diam., bears N. 67° W. 96 lks. dist., mkd. $\frac{1}{4}$ S20 BT.

A sawed cedar stump, 30 ins. diam., bears S. 68° W., 76 lks. dist., mkd. $\frac{1}{4}$ S29 BT.

The corner is situated on a SE. slope, in old logged and burned area, 5 lks. W. of a barbed wire fence which bears N. and S.

GENERAL DESCRIPTION

The line between sections 3 and 4, T. 23 S., R. 4 W., is located in Douglas County about 35 miles northeasterly from the City of Roseburg, Oregon, and 5 miles north of the community of Elkhead. The terrain is mountainous in nature and the elevation ranges from