

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, South Boundary, T. 24 S., R. 2 W.

CHAINS

Dependent Resurvey of the South Boundary of T. 24 S.,  
R. 2 W.

(Restoring the 1883 survey by John A. McQuinn)

## Memorandum

The intermediate corners along this line which were established by McQuinn formerly referred only to T. 24 S., R. 2 W. The purported retracement of the south boundary of sec. 31 and the reported establishment of closing corners on the boundary by Hezekiah Johnson in 1900 having proved to be fictitious, the McQuinn corners except for the south  $\frac{1}{4}$  sec. cor. of sec. 31 and the south  $\frac{1}{4}$  sec. cor. of sec. 36, are changed in 1963 to corners of maximum control in order to provide a basis for Consent Decree "Civil No. 60-135, Oregon".

Beginning at the cor. of Tps. 24 and 25 S., R. 2 W., on the W. bdy. of sec. 31, T. 24 S., R. 1 W., determined at record distance from the original bearing trees:

- A fir, 30 ins. diam., bears N.  $27^{\circ}$  E., 16 lks. dist., with blaze healed. (Record bearing, N.  $20^{\circ}$  E.)
- A rotted stump, bears S.  $56^{\circ}$  E., 22 lks. dist. (Record bearing, S.  $60\frac{1}{2}^{\circ}$  E.)
- A fir, 18 ins. diam., bears S.  $57\frac{1}{2}^{\circ}$  W., 32 lks. dist., with partial scribe marks visible on blaze under 68 yrs. of overgrowth. (Record bearing, S.  $63^{\circ}$  W.)
- A fir, 18 ins. diam., bears N.  $17^{\circ}$  W., 15 lks. dist., with scribe marks 36 T24 R2 BT visible on old bark blaze. (Record bearing N.  $25^{\circ}$  W.)

At the corner point

Set an iron post, 36 ins. long, 3 ins. diam., 8 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T 24 S	
R 2 W	T 24 S
S 36	R 1 W
S 1	S 31
T 25 S	
1951	

from which bearing trees marked in 1951:

- A fir, 18 ins. diam., bears N.  $35\frac{1}{2}^{\circ}$  W., 28 lks. dist., mkd. T24S R2W S36 BT.
- A fir, 20 ins. diam., bears S.  $44\frac{1}{2}^{\circ}$  W., 46 lks. dist., mkd. T25S R2W S1 BT.

S.  $80^{\circ} 35'$  W., bet. secs. 1 and 36, marking and blazing the true line.

Descend 122 ft. over NW. slope, through heavy timber and dense undergrowth.

4.93 Ravine, course N.  $10^{\circ}$  W.; asc. 137 ft. over NE. slope.

11.65 Top of ascent; desc. 41 ft. along broken N. slope.