

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, South Boundary, T. 24 S., R. 2 W.

CHAINS

- 19.80 Spur, slopes N. 50° W.; desc. 195 ft. over NW. slope.
- 27.00 Spur, slopes N. 40° W.; desc. 134 ft. over NW. slope
- 30.44 Foot of descent; asc. 45 ft. over NE. slope.
- 34.09 Spur, slopes N.; desc. 116 ft. along broken N. slope.
- 37.81 Point for the $\frac{1}{4}$ sec. cor. of sec. 36 only, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 1 in. diam. 28 ins. in the ground, with brass cap mkd.

$\frac{1}{4}$ S 36
1951

from which bearing trees marked in 1951:

A fir 20 ins. diam. bears N. 35° E., 21 lks.
dist. mkd. $\frac{1}{4}$ S36 BT.

A fir, 16 ins. diam. bears N. 63° W., 56 lks.
dist., mkd. $\frac{1}{4}$ S36 BT.

Descend 188 ft. along broken N. slope.

- 59.97 Ridge, bears N. 40° W. and S. 40° E.; desc. 226 ft. over SW. slope.
- 69.37 Spur, slopes S. 35° W.; desc. 234 ft. over NW. slope.
- 75.62 Point for the cor. of secs. 35 and 36, at proportionate distance; there is no remaining evidence of the original corner. This now becomes the cor. of secs. 1, 2, 35, and 36.

Set an iron post, 36 ins. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T 24 S | R 2 W
S 35 | S 36

S 2 | S 1
T 25 S
1951

from which bearing trees marked in 1963:

A fir, 35 ins. diam., bears N. 56° E., 184 lks.
dist., mkd. T24S R2W S36 BT.

A pine stump, 44 ins. diam., bears S. 28° E.,
28 lks. dist., mkd. T25S R2W S1 BT.

A pine stump, 42 ins. diam., bears S. $23\frac{1}{2}^{\circ}$ W.,
46 lks. dist., mkd. T25S R2W S2 BT.

A fir, 35 ins. diam., bears N. $83\frac{1}{2}^{\circ}$ W., 63 lks.
dist., mkd. T24S R2W S35 BT.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, sugar pine, cedar, maple, yew,
and madrone, Undergrowth, vine maple, salal, huckle-
berry, and Oregon grape.