

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, South Boundary, T. 24 S., R. 2 W.

CHAINS

- A cedar, 37 ins. diam., bears S. 38° E., 32 lks. dist., mkd. T25S R2W S2 BT. (1963 bearing tree.)
- A cedar, 35 ins. diam., bears S. 46¼° W., 36 lks. dist., mkd. T25S R2W S3 BT. (1963 bearing tree.)
- A cedar, 18 ins. diam., bears N. 57° W., 77 lks. dist., mkd. T24S R2W S34 BT. (1951 bearing tree.)

Land, mountainous.  
 Soil, rocky clay loam.  
 Timber, fir, hemlock, sugar pine, cedar, maple, yew, and madrone; undergrowth, vine maple, salal, huckleberry and Oregon grape.

S. 80° 35' W., bet. secs. 3 and 34.

Ascend 742 ft. over NE. slope, through heavy timber and dense undergrowth.

- 12.84 Head of a ravine, course N. 60° E.
- 23.52 Ridge, bears N. 40° W., and S. 40° E.; desc. 345 ft. over SW. slope.
- 37.81 Point for the ¼ sec cor. of sec. 34, at proportionate distance; there is no remaining evidence of the original corner. This now becomes the ¼ sec. cor. of secs. 3 and 34.

Set an iron post, 36 ins. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\frac{\frac{1}{4} \text{ S } 34}{\text{S } 3}$$
 1951

from which

- A fir, 28 ins. diam., bears N. 48½° W., 81 lks. dist, mkd. ¼ S34 BT. (1951 bearing tree.)
- A fir, 25 ins. diam., bears S. 48¼° W., 53 lks. dist,, mkd. ¼ S3 BT. (1963 bearing tree.)

Descend 387 ft. over SW. slope.

- 53.74 Branch, 1 lk. wide, course S. 50° W.
- 55.82 Branch, 1 lk. wide, course S. 30° E.; asc. 336 ft. over E. slope.
- 65.62 Top of ascent; desc. 86 ft. along S. slope.
- 75.62 Point for the cor. of secs. 33 and 34, at proportionate distance; there is no remaining evidence of the original corner. This now becomes the cor. of secs. 3, 4, 33, and 34.

Set an iron post, 36 ins. long, 2 ins. dian., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{r|l} \text{T } 24 \text{ S} & \text{R } 2 \text{ W} \\ \text{S } 33 & \text{S } 34 \\ \hline \text{S } 4 & \text{S } 3 \\ \text{T } 25 \text{ S} & \\ 1951 & \end{array}$$

from which