

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, South Boundary, T. 24 S., R. 2 W.

CHAINS	Timber, fir, hemlock, sugar pine, cedar, maple, yew, and madrone; undergrowth, vine maple, salal, huckleberry and Oregon grape.
	S. 88° 34' W., bet. secs. 5 and 32.
	Descend 38 ft. over W. slope, along S. edge of logging.
2.02	Branch, 3 lks. wide, course S.; asc. 35 ft. over E. slope
6.67	Spur, slopes S.; desc. 700 ft. over rocky W. slope.
29.67	Ravine, course S.; desc. 33 ft. over bench.
34.56	Spring branch, 2 lks. wide, course S.
37.44	The $\frac{1}{4}$ sec. cor. of sec. 32, determined from the original NW. bearing tree:
	A fallen hemlock, 24 ins. diam., the stump hole of which bears N. 60° W., 44 lks. dist., with blaze burnt.
	This now becomes the $\frac{1}{4}$ sec. cor. of secs. 5 and 32.
	At the corner point
	Set an iron post, 36 ins. long, 1 in. diam., 20 ins. in the ground to solid rock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	$\frac{1}{4}$ S 32 S 5 1951
	from which
	A maple, 30 ins. diam., bears N. 76° E., 46 lks. dist., mkd. $\frac{1}{4}$ S32 BT. (1951 bearing tree.)
	A cedar, 12 ins. diam., bears S. 27° E., 126 lks. dist., mkd. $\frac{1}{4}$ S5 BT. (1963 bearing tree.)
	S. 85° 32' W., beginning new measurement.
	Descend 53 ft. over SW. slope.
18.46	Harrington Creek, 7 lks. wide, course S.; asc. 278 ft. over SE. slope.
38.55	The cor. of secs. 31 and 32, determined from the original bearing trees:
	A fir, 50 ins. diam., bears N. 25° E., 50 lks. dist., with partial scribe marks on old bark blaze. (In 1951) (Record bearing, N. 20° E.) In 1963, this is a sawed fir stump with no marks remaining.
	A hemlock, 20 ins. diam., bears N. 85° E., 70 lks. dist., mkd. T25 R2 S5 BT. (Record, S. 85° E., 78 lks. dist.)
	A fir, 50 ins. diam., bears S. 55° 45' W., 20 lks. dist., with partial scribe marks on old bark blaze. (Record bearing, S. 50° W.)