

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, South Boundary, T. 24 S., R. 2 W.

CHAINS

A fir, 50 ins. diam., bears S. $41\frac{1}{4}^{\circ}$ W., 51 lks. dist., mkd. T25S R3W S1 BT. (1951 bearing tree.)

A sawed fir stump, 48 ins. diam., bears N. 52° W., 64 lks. dist., with blaze burnt. (Original bearing tree; 1943 record bearing, N. $50\frac{1}{2}^{\circ}$ W.)

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, yew, madrone, and dogwood; undergrowth, vine maple, salal, huckleberry, and Oregon grape.

Dependent Resurvey of a Portion of the East Boundary of T. 24 S., R. 2 W.

(Restoring the 1883 survey by John A. McQuinn and the 1896 retracement by Carl S. Nicklin)

From the cor. of Tps. 24 and 25 S., R. 2 W., on the E. bdy. of the Tp.

N. 0° 17' W., along the E. bdy. of sec. 36, marking and blazing the true line.

Descend 447 ft. over N. slope, through heavy timber and dense undergrowth.

9.71 Creek, 10 lks. wide, course W.; asc. 889 ft. over S. slope.

36.13 The $\frac{1}{4}$ sec. cor. of sec. 36, determined at record bearing and distance from the 1883 SW. bearing tree and the 1896 NE. bearing tree.

from which the old bearing trees:

A fir, 40 ins. diam., bears N. 29° E., 30 lks. dist., blaze healed. (1896 BT.)

A fir, 8 ins. diam., bears S. 73° W., 16 lks. dist., blaze healed. (1883 BT.)

At the corner point

Set an iron post, 36 ins. long, 1 in. diam., 6 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 36 \\ 1951 \end{array}$$

from which

A fir, 16 ins. diam., bears N. 20° W., 19 lks. dist., mkd. $\frac{1}{4}$ S36 BT.

N. 5° 51' E., beginning new measurement.

Ascend 26 ft. over S. slope.

0.94 Ridge, bears N. 70° W. and S. 70° E.; desc. 457 ft. over NE. slope.