

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, East Boundary T. 24 S., R. 2 W.

CHAINS

- 9.67 Ravine, course N. 30° E.; desc. 205 ft. over broken E. slope.
- 14.08 Spur, slopes N. 40° E.
- 16.02 Branch 1 lk. wide, course N. 60° E.; asc. 41 ft. over E. slope.
- 20.30 Top of ascent, desc. 359 ft. over NE. slope.
- 24.44 The closing cor. of secs. 30 and 31, T. 24 S., R. 1 W. bears East, 1.56 chains dist.

The closing cor. is determined at record bearing and distance from the original SE. bearing tree:

A hemlock, 14 ins. diam., bears S. 43° E., 21 lks. dist., with scribe marks S3 visible on partially healed blaze.

- 31.45 Branch, 1 lk. wide, course N. 10° E.; desc. 53 ft. over broken E. slope.

- 36.01 The cor. of secs. 25 and 36, determined from the NE. and SE. bearing trees:

A cedar, 44 ins. diam., bears N. 40° E., 52 lks. dist., with scribe marks S20 T24 R BT visible.

A fallen cedar, 46 ins. diam., bears S. 25° E., 15 lks. dist., blaze rotted. (Record bearing S. 75° E.)

At the corner point

Set an iron post, 36 ins. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T 24 S	T 24 S
S 25	R 1 W
S 36	S 30
R 2 W	

1951

from which

A cedar, 10 ins. diam., bears N. 78° W., 97 lks. dist., mkd. T24S R2W S25 BT.

A cedar, 36 ins. diam., bears S. 32° W., 122 lks. dist., mkd. T24S R2W S36 BT.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, sugar pine, yew, madrone, and dogwood; undergrowth, vine maple, salal, huckleberry, and Oregon grape.

Dependent Resurvey of a Portion of the West Boundary
of T. 24 S., R. 2 W.

(Restoring the 1871 survey by William H. Byars)

from the cor. of Tps. 24 and 25 S., Rs. 2 and 3 W.

N. 1° 26' W., bet. secs. 31 and 36, marking and blazing the true line.