

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, West Boundary, T. 24 S., R. 2 W.

CHAINS

bark blaze. (Record, a spruce, 30 ins. diam., bears N. 72° W., no dist. given)

At the corner point

Set an iron post, 36 ins. long, 2 ins. diam., 22 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T 24 S	
R 3 W	R 2 W
S 25	S 30
S 36	S 31
1951	

from which

A fir, 24 ins. diam., bears N. 82° E., 72 lks. dist., mkd. T24S R2W S30 BT.

A fir, 24 ins. diam., bears S. $26\frac{1}{2}^{\circ}$ E., 143 lks. dist., mkd. T24S R2W S31 BT.

A sawed fir stump, 32 ins. diam., bears S. $50\frac{1}{2}^{\circ}$ W., 52 lks. dist., mkd. T24S R3W S36 BT.

A fir, 22 ins. diam., bears N. $41\frac{1}{4}^{\circ}$ W., 23 lks. dist., mkd. T24S R3W S25 BT.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, yew, madrone, and dogwood; undergrowth, vine maple, salal, huckleberry, Oregon grape, and rhododendron.

Dependent Resurvey of a Portion
of the Subdivisional Lines
of T. 24 S., R. 2 W.

(Restoring the 1883 survey by John A. McQuinn
and the 1894 survey by Henry L. Chandler.)

Memorandum

The south, east, and west boundaries of Tracts Nos. 37, 38, 39, and 40 coincide with the section lines and comprise the south portion of secs. 33, 34, 35, and 36, respectively. The northerly tract corners are established in 1963 at points on the section lines to accord with the boundaries of federal public lands determined in Consent Decree "Civil No. 60-135, Oregon". The north boundaries are surveyed directly between these corners, as hereinafter described.

From the cor. of secs. 1, 2, 35, and 36, on the S. bdy. of the Tp.

N. $21^{\circ} 37'$ E., bet. secs. 35 and 36, marking and blazing the true line.

Descend slightly over broken NW. slope, through heavy timber and dense undergrowth.

6.70 Small spur, slopes S. 80° W.; desc. slightly over NW. slope.