

Dependent Resurvey, Subdivisional Lines, T. 24 S., R. 2 W.

CHAINS

N. 0° 47' E., beginning new measurement.

Ascend 220 ft. over SW. slope.

9.65 Spur, slopes W.; desc. 151 ft. over NW. slope.

15.94 Ravine, course W.; asc. 96 ft. over SW. slope.

20.79 Spur, slopes W.; desc. 98 ft. over NW. slope.

25.61 Ravine, course W.; asc. 91 ft. over SW. slope.

28.16 Spur, slopes W.; desc. 133 ft. over NW. slope.

32.07 Foot of descent; asc. 73 ft. over SW. slope.

38.45 The cor. of secs. 25, 26, 35, and 36, determined at record distance from the original bearing trees:

A fir, 28 ins. diam., bears N. 60° E., 35 lks. dist., blaze healed, edge of face under 57 yrs. overgrowth. (Record bearing, N. 55° E.)

A hemlock, 20 ins. diam., bears S. 57° E., 53 lks. dist., partial scribe marks visible. (Record bearing, S. 63° E.)

A down fir, 30 ins. diam., bears S. 66 $\frac{1}{4}$ ° W., 22 lks. dist., blaze healed. (Record bearing, S. 81° W.)

A down fir, 20 ins. diam., bears N. 75° W., 53 lks. dist., blaze healed.

At the corner point

Set an iron post, 36 ins. long, 2 ins. diam., 24 ins. in the ground to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T 24 S	R 2 W
S 26	S 25
S 35	S 36
1951	

from which

A hemlock, 12 ins. diam., bears N. 30 $\frac{1}{2}$ ° E., 38 lks. dist., mkd. T24S R2W S25 BT.

A fir, 20 ins. diam., bears S. 79° E., 68 lks. dist., mkd. T24S R2W S36 BT.

A hemlock, 14 ins. diam., bears S. 67 $\frac{1}{2}$ ° W., 71 lks. dist., mkd. T24S R2W S35 BT.

A hemlock, 14 ins. diam., bears N. 67° W., 97 lks. dist., mkd. T24S R2W S26 BT.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, sugar pine, yew, madrone, and dogwood; undergrowth, vine maple, salal, huckleberry, and Oregon grape.

From the cor. of secs. 25 and 36, on the E. bdy. of the Tp.

S. 67° 52' W., bet. secs. 25 and 36.