

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 24 S., R. 2 W.

CHAINS

Land, mountainous.
Soil, rocky clay loam.
Timber, fir, hemlock, cedar, sugar pine, yew, madrone, chinquapin, and dogwood; undergrowth, vine maple, salal, huckleberry, and Oregon grape.

From the cor. of secs. 3, 4, 33, and 34, on the S. bdy. of the Tp.

N. 5° 41' E., bet. secs. 33 and 34.

Ascend 124 ft. over SW. slope, changing to gradual S. slope, through heavy timber and dense undergrowth.

7.21 Point for the NE. cor. of Tract No. 37, sec. 33.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 24 S R 2 W
S 33 S 34
TR 37 TR 38
1963

from which

A cedar, 11 ins. diam., bears S. $66\frac{1}{2}^{\circ}$ W., 30 lks. dist., mkd. TR37 S33 BT.

A hemlock, 11 ins. diam., bears N. 19° W., 7 lks. dist., mkd. S33 BT.

Ascend 100 ft. over S. slope, becoming steeper.

12.96 Point for the NW. cor. of Tract No. 38, sec. 34.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 S R 2 W
S 33 S 34
TR 38
1963

from which

A fir, 30 ins. diam., bears N. 70° E., 77 lks. dist., mkd. S34 BT.

A cedar, 30 ins. diam., bears S. 6° W., 37 lks. dist., mkd. TR38 S34 BT.

Ascend 195 ft. over steep S. slope.

17.65 Spur, slopes S. 40° E.; desc. 40 ft. over NE. slope.

23.80 Ravine, course S. 35° E.; asc. 270 ft. over SW. slope, changing to SE. slope.

30.20 Spur, slopes S. 25° E.; desc. 45 ft. over NE. slope.

33.45 Branch, 4 lks. wide, course S. 50° E.; asc. 455 ft. over SE. slope.

43.59 The $\frac{1}{4}$ sec. cor. of secs. 33 and 34, monumented with a basalt stone, 13 x 13 x 9 ins., firmly set marked $\frac{1}{4}$ on W. face, from which the original bearing trees: