

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 24 S., R. 2 W.

CHAINS

A fir, 18 ins. diam., bears N.  $70^{\circ}$  W., 11 lks. dist., blaze healed. (Record bearing, N.  $75^{\circ}$  W.)

A fir snag, 12 ins. diam., bears S.  $36^{\circ}$  E., 22 lks. dist., blaze partially healed, with scribe marks  $\frac{1}{4}$  S visible. (Record, bears S.  $35^{\circ}$  E., 25 lks. dist.)

At the corner point

Set an iron post, 36 ins. long, 1 ins. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 33 \text{ | } \text{S } 34 \\ 1951 \end{array}$$

from which

A fir, 28 ins. diam., bears S.  $89^{\circ}$  E., 55 lks. dist., mkd.  $\frac{1}{4}$  S34 BT.

Bury the original corner stone alongside the iron post.

N.  $0^{\circ}$  26' W., beginning new measurement.

Ascend 92 ft. over S. slope.

- 4.65 Ridge, bears E. and W.; desc. 495 ft. over N. slope.
- 22.88 Branch, 1 lk. wide, course N.  $80^{\circ}$  E.; asc. 66 ft. over SE. slope.
- 29.79 Spur, slopes E.; desc. 176 ft. over NW. slope.
- 37.95 The cor. of secs. 27, 28, 33, and 34, monumented with a basalt stone, 16 x 14 x 10 ins., firmly set, marked with 1 notch on S. and 3 notches on E. edges, from which the original bearing trees:

A chinquapin, 10 ins. diam., bears N.  $31^{\circ}$  E., 18 lks. dist., partial scribe marks visible in rotted blaze. (Record dist., 20 lks.)

A hemlock, 12 ins. diam., bears S.  $25\frac{1}{4}^{\circ}$  W., 14 lks. dist., blaze healed. (Record bearing, S.  $28^{\circ}$  E.)

A hemlock, 12 ins. diam., bears S.  $15\frac{1}{2}^{\circ}$  W., 17 lks. dist., scribe marks T24S R2W S33 visible. (Record bearing, S.  $15^{\circ}$  W.)

A hemlock, 12 ins. diam., bears N.  $64\frac{1}{2}^{\circ}$  W., 14 lks. dist., blaze healed. (Record bearing, N.  $60^{\circ}$  W.)

At the corner point

Set an iron post, 36 ins. long, 2 ins. diam., 24 ins. in the ground, to solid rock and in a mound of stone, 4 ft. base to top, with brass cap mkd.

$$\begin{array}{c} \text{T } 24 \text{ S | R } 2 \text{ W} \\ \text{S } 28 \text{ | S } 27 \\ \text{S } 33 \text{ | S } 34 \\ 1951 \end{array}$$