

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 24 S., R. 2 W.

CHAINS	<p>S. 89° 53' W., beginning new measurement.</p> <p>Descend 80 ft. over SW. slope.</p> <p>7.19 Ravine, course SW.; asc. 10 ft. over SE. slope.</p> <p>8.18 Top of ascent; desc. 45 ft. over SW. slope.</p> <p>12.51 Ravine, course SW.; asc. 7 ft. over SE. slope.</p> <p>14.00 Top of ascent; desc. 134 ft. over SW. slope.</p> <p>20.36 Branch, 3 lks. wide, course S. 40° E.; asc. 172 ft. over SE. slope</p> <p>27.72 Spur, slopes, S.; desc. 110 ft. over SW. slope.</p> <p>32.06 Branch, 10 lks. wide, course S. 20° E.; asc. 269 ft. over E. slope.</p> <p>39.09 The cor. of secs. 27, 28, 33, and 34.</p> <p>Land, mountainous. Soil, rocky clay loam. Timber, fir, hemlock, cedar, sugar pine, yew, madrone, and chinquapin; undergrowth, vine maple, salal, huckleberry, and Oregon grape.</p> <hr/> <p>From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp.</p> <p>N. 2° 56' E., bet. secs. 32 and 33.</p> <p>Ascend 100 ft. over SW. slope, through heavy timber and dense undergrowth.</p> <p>4.25 Branch, 4 lks. wide, course S. 60° W.; asc. 255 ft. over S. slope, changing to broken SW. slope.</p> <p>6.00 Leave timber; thence along E. edge of logged area.</p> <p>19.66 Point for the NW. cor. of Tract No. 37, sec. 33.</p> <p>Set an iron post, 36 ins. long 2 ins. diam., 30 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 24 S R 2 W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">S 32</td> <td style="padding-left: 5px;">S 33</td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;"></td> <td style="padding-left: 5px;">TR 37</td> </tr> </table> <p>1963</p> </div> <p style="text-align: right;"><i>SEE ALSO WEYERHAEUSER NOTES IN C.S. 59/11</i></p> <p>from which</p> <p style="padding-left: 40px;">A hemlock, 10 ins. diam., bears N. 81½° E., 94 lks. dist., mkd. S33 BT.</p> <p style="padding-left: 40px;">A yew, 9 ins. diam., bears S. 47½° E., 102 lks. dist., mkd. TR37 S33 BT.</p> <p>Ascend 140 ft. over broken SW. slope.</p> <p>27.90 Trail, bears N. 20° W. and S. 20° E.</p> <p>31.00 Ridge, bears N. 35° W. and S. 35° E.; desc. 37 ft. over NE. slope.</p> <p>33.63 Point for the ¼ sec. cor. of secs. 32 and 33, at pro-</p>	S 32	S 33		TR 37
S 32	S 33				
	TR 37				