

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 24S., R. 2 W.

CHAINS

portionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 1 ins. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 32 \frac{1}{4} \text{ S } 33 \\ 1951 \end{array}$$

from which

A cedar, 13 ins. diam., bears S. $82\frac{1}{4}^{\circ}$ E., 43 lks. dist., mkd. $\frac{1}{4}$ S33 BT. (1963 bearing tree.)

A yew, 14 ins. diam., bears N. $56\frac{1}{4}^{\circ}$ W., 27 lks. dist., mkd. $\frac{1}{4}$ S32 BT. (1951 bearing tree, 16 ins. diam., in 1963.)

Descend 179 ft. over NE. slope; edge of logging is about 3 chs. W. of line.

41.00 Branch, 4 lks. wide, course E.; asc. 131 ft. over SW. slope.

49.50 Spur, slopes E.; asc. 96 ft. along broken E. slope.

67.26 Point for the cor. of secs. 28, 29, 32, 33, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 36 ins. long, 2 ins. diam., 24 ins. in the ground to solid rock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

$$\begin{array}{c} \text{T } 24 \text{ S } \text{ R } 2 \text{ W} \\ \text{S } 29 \text{ S } 28 \\ \text{S } 32 \text{ S } 33 \\ 1951 \end{array}$$

from which

A fir, 11 ins. diam., bears N. 46° E., 42 lks. dist., mkd. T24S R2W S28 BT.

A fir, 14 ins. diam., bears S. 19° E., 33 lks. dist., mkd. T24S R2W S33 BT.

A fir, 16 ins. diam., bears S. 75° W., 15 lks. dist., mkd. T24S R2W S32 BT.

A fir, 12 ins. diam., bears N. 7° W., 30 lks. dist., mkd. T24S R2W S29 BT.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, sugar pine, yew, madrone, chinquapin, and dogwood; undergrowth, vine maple, salal, huckleberry, and Oregon grape.

From the cor. of secs. 27, 28, 33, and 34.

N. $89^{\circ} 09'$ W., bet. secs. 28 and 33.

Ascend 37 ft. over NE. slope, through heavy timber and dense undergrowth.