

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines T. 24 S., R. 2 W.

CHAINS	
6.50	Top of ascent; desc. 7 foot. over NW. slope.
7.95	Branch, 3 lks. wide, course NE.; asc. 235 ft. over NE. slope.
8.94	Spur, slopes NE.
21.00	Top of ascent; desc. 39 ft. over NW. slope.
23.77	Branch, 4 lks. wide, course NE.; asc. 462 ft. over E. slope.
37.40	The $\frac{1}{4}$ sec. cor. of secs. 28 and 33, monumented with a basalt stone, 15 x 8 x 6 ins., firmly set, marked $\frac{1}{4}$ on N. face, from which the original bearing trees. A fir, 50 ins., diam., bears N. $64\frac{1}{2}^{\circ}$ W., 58 lks. dist., blaze healed. (Record bearing, N. 70° W.) A hemlock, 12 ins. diam., bears S. $68^{\circ} 45'$ W., 20 lks. dist., blaze partially healed, partial scribe marks visible. (Record, S. 74° W., 28 lks. dist.) At the corner point Set an iron post, 36 ins. long, 1 in. diam., 12 ins. in the ground to solid rock, and in a mound of stone, 4 ft. base to top, with brass cap mkd. $\frac{1}{4} \begin{array}{l} S 28 \\ S 33 \end{array}$ from which A fir, 60 ins. diam., bears S. $0\frac{1}{4}^{\circ}$ W., 63 lks. dist., mkd. $\frac{1}{4}$ S33 BT. Bury the original corner stone alongside the iron post. <hr/> S. $54^{\circ} 22'$ W., beginning new measurement. Ascend 86 ft. over E. slope.
7.93	Spur, slopes S.; desc. 20 ft. over SE. slope.
11.97	Ravine, course SE.; asc. 145 ft. over SE. slope.
18.05	Ridge, bears NW. and SE.; desc. 231 ft. over SW. slope.
28.00	Ravine, course SE.; asc. 4 ft. over SE. slope.
28.81	Spur, slopes SE.; desc. 192 ft. over SW. slope.
37.51	Branch, 4 lks. wide, course SE.; asc. 319 ft. over E. slope.
46.41	The cor. of secs. 28, 29, 32, and 33. Land, mountainous. Soil, rocky clay loam. Timber, fir, hemlock, cedar, sugar pine, yew, madrone, chinquapin, and dogwood; undergrowth, vine maple, salal, huckleberry, Oregon grape, and rhododendron.