

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines. T. 24 S., R. 2 W.

CHAINS

partially-healed upper blaze, the lower blaze healed.

At the corner point

Set an iron post, 36 ins. long, 1 in. diam., 20 ins. in the ground to solid rock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 31 \mid \text{S } 32 \\ 1951 \end{array}$$

from which

A fir, 28 ins., diam., bears N. $71\frac{1}{2}^{\circ}$ E., 85 lks. dist., mkd. $\frac{1}{4}$ S32 BT.

A fir, 32 ins. diam., bears S. $77\frac{1}{2}^{\circ}$ W., 54 lks. dist., mkd. $\frac{1}{4}$ S31 BT.

N. 0° 31' E., beginning new measurement.

Ascend 216 ft. over SW. slope.

12.21 Branch, 6 lks. wide, course SW.; asc. 701 ft. over SW. slope.

26.24 Graded and graveled logging road, bears N. 60° W. and S. 60° E.

37.87 The cor. of secs. 29, 30, 31, and 32, determined at record distance from the original bearing trees:

A fir, 42 ins. diam., bears N. 59° E., 114 lks. dist., with partial scribe marks on old bark blaze, breast high. I reblaze and remark. T24S R2W S29 BT. (Record bearing, N. 55° E.)

A fir, dead and fallen, 30 ins. diam., bears S. 50° E., 65 lks. dist., with partial scribe marks on old bark blaze. (Record bearing, S. 30° E.)

A fir, 44 ins. diam., bears S. 77° W., 65 lks. dist., with partial scribe marks on old bark blaze, breast high. I reblaze and remark, T24S R2W S31 BT. (Record bearing, S. 83° W.)

A fir, 46 ins. diam., bears N. 8° W., 63 lks. dist., blaze healed. (Record bearing N. 15° W.)

At the corner point

Set an iron post, 36 ins. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \text{T } 24 \text{ S} \mid \text{R } 2 \text{ W} \\ \text{S } 30 \mid \text{S } 29 \\ \text{S } 31 \mid \text{S } 32 \\ 1951 \end{array}$$

from which

A fir, 48 ins. diam., bears S. 74° E., 25 lks.