

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivison Lines. T. 24 S., R. 2 W.

CHAINS

22.70 Foot of descent; asc. 22 ft. over SE. slope.

26.65 Top of ascent; desc. 56 ft. over SW. slope.

30.83 Ravine, course S.; asc. 40 ft. over SE. slope.

33.50 Top of ascent; desc. 16 ft. over SW. slope.

39.48 The cor. of secs. 29, 30, 31, and 32.

Land, mountainous.
Soil, rocky clay loam.
Timber, fir, hemlock, cedar, yew, madrone, and dogwood;
undergrowth, vine maple; salal, huckleberry, Oregon
grape and rhododendron.

N. 85° 45' W., bet. secs. 30 and 31.

Descend 5 ft. over SW. slope, along N. edge of logging

1.33 Ravine, course SE.; asc. 185 ft. over E. slope.

14.75 Ridge, the divide bet. Calapooya Creek and Rock Creek,
bears NE. and SW.; desc. 190 ft. over NW. slope.

20.45 Ravine, course NW.; desc. 563 ft. over NW. slope.

35.07 Branch, 2 lks. wide, course N.; asc. 143 ft. over NE.
slope.

39.40 Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31, at pro-
portionate distance; there is no remaining evidence of
the original corner.

Set an iron post, 36 ins. long, 1 ins. diam., 18 ins.
in the ground, to solid rock and in a mound of stone,
4 ft. base to top, with brass cap mkd.

$$\frac{1}{4} \begin{array}{l} S 30 \\ S 31 \end{array}$$

from which

A fir, 36 ins. diam., bears N. 34 $\frac{1}{2}$ ° E., 103 lks.
dist., mkd. $\frac{1}{4}$ S30 BT.

A fir, 40 ins. diam., bears N. 26° W., 131 lks.
dist., mkd. $\frac{1}{4}$ S30 BT.

No bearing tree available S. of line.

Ascend 2 ft. over NE. slope, through N. edge of logging.

39.70 Spur, slopes N.; desc. 252 ft. over NW. slope.

51.66 Branch, 5 lks. wide, course N.; asc. 639 ft. over NE.
slope.

70.00 Spur, slopes N.; desc. 77 ft. over NE. slope.

78.22 The cor. of secs. 25, 30, 31, and 36, on the W. bdy. of
the Tp.

Land, mountainous.
Soil, rocky clay loam.
Timber, fir, hemlock, cedar, yew, madrone, and dogwood;
undergrowth, vine maple, salal, huckleberry, Oregon