

Dependent Resurvey, Subdivisional Lines, T. 24 S., R. 6 W.

CHAINS

S 17	S 16
S 20	S 21
T 24 S	R 6 W
1959	

from which the remaining original bearing trees:

A madrone, 28 ins. diam., bears S.  $13^{\circ}$  W., 41 lks. dist., mkd. with an old blaze. Re-marked by Byron, T24S R6W S21 CS BT, in the bark, beside the old blaze. (Record bearing and distance, S.  $15\frac{1}{2}^{\circ}$  E., 39 lks.)

A burned out fir stump, 36 ins. diam., bears N.  $82\frac{1}{2}^{\circ}$  W., 60 lks. dist., no marks remaining.

and bearing trees marked by Byron:

A sawed fir stump, 34, ins. diam., bears N.  $82\frac{1}{2}^{\circ}$  E., 89 lks. dist., with a steel spike driven into the center of the stump.

A maple, 13 ins. diam., bears S.  $44\frac{1}{4}^{\circ}$  W., 37 lks. dist., mkd. S20 CS BT, on an open blaze.

and a bearing object, marked by Byron,

A sandstone outcropping, 5 x 5 x 3 ft. above ground, bears S.  $70^{\circ}$  W., 20 lks. dist., mkd. BXO on N. face.

No other trees available.

N.  $0^{\circ}$  04' W., bet. secs. 16 and 17.

Descend 50 ft. over NE. slope, through scattering to dense undergrowth, across old logged and burned area.

- 1.05 Ravine, drains E.; asc. 115 ft. over SE. slope.
- 4.90 Spur, slopes E.; desc. 75 ft. over NE. slope.
- 7.30 Ravine, drains S.  $75^{\circ}$  E.; asc. 40 ft. over SE. slope.
- 10.00 Spur, slopes SE.; desc. 30 ft. over NE. slope.
- 12.00 Ravine, drains SE.; asc. 400 ft. over SE. slope.
- 19.90 Spur, slopes S.  $80^{\circ}$  E.; desc. 30 ft. over broken NE. slope.
- 30.90 Ravine, steep and rocky, drains S.  $40^{\circ}$  E.; asc. 430 ft. over SE. slope.
- 39.40 Spur, slopes S.  $60^{\circ}$  E.; desc. 5 ft. along E. slope.
- 40.12 Point for the  $\frac{1}{4}$  sec. cor. of secs. 16 and 17, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap marked

$\frac{1}{4}$	
S 17	S 16
T 24 S	R 6 W
1963	

from which