

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines. T. 24 S., R. 6 W.

CHAINS

Alder, oak, and yew; undergrowth, young timber, hazel, arrowwood, ceanothus, Oregon grape, salal, scotch broom, greasewood, berries, vines, ferns, and weeds.

From the cor. of secs. 9, 10, 15, and 16, perpetuated by James Byron, Deputy County Surveyor, in 1958, with an iron post, 1 in. diam., protruding 14 ins. above ground, firmly set, with brass cap marked

S 9	S 10
S 16	S 15
T 24 S	R 6 W
1958	

from which the remaining bearing trees mkd. by Whipple:

A dead cedar, 40 ins. diam., bears S. $7\frac{3}{4}^{\circ}$ E., 176 lks. dist., mkd. with an opened blaze.
(Record bearing and dist., S. $10\frac{1}{2}^{\circ}$ E., 156 lks.)

A cedar, blown down, 48 ins. diam., bears S. 84° 10' W., 181 lks. dist., mkd. T 2 S, on opened blaze.

and bearing trees mkd. by Byron, in 1958:

An apple tree, 12 ins. diam., bears N. $61\frac{1}{4}^{\circ}$ E., 191 lks. dist., bark scribed S10 CS BT.

A white oak, 18 ins. diam., bears S. 86° E., 388 lks. dist., mkd. T24S R6W S15 CS BT, on partially healed blaze.

A cedar, 6 ins. diam., bears S. $20\frac{1}{4}^{\circ}$ W., 88 lks. dist., mkd. with a healed blaze.

A fork of a white oak, 22 ins. diam., bears S. 88° W., 302 lks. dist., mkd. T24S R6W S16 BT, on nearly healed blaze.

N. 89° 27' W., bet. secs. 9 and 16.

Ascend 50 ft. over broken and rolling SE. slope, through scattering timber, across a generally open prairie.

11.05 Woven wire fence, bears N. and S.

18.00 Spur, slopes S., woven wire fence bears N. and S.; desc. 75 ft. over SW. slope, entering moderate undergrowth.

20.44 Point for the E 1/16 sec. cor. of secs. 9 and 16.

Set an iron post, 28 ins. long $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

E 1/16	S 9
	S 16
T 24 S	R 6 W
1963	

from which

A cedar, 15 ins. diam., bears N. 17° E., 98 lks. dist., mkd. E 1/16 S9 BT.

A fir, 15 ins. diam., bears S. 33° E., 128 lks. dist., mkd. E 1/16 S16 BT.