

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 24 S., R. 6 W.

CHAINS	
21.30	Creek, 1 lk. wide, course S. 20° W.; asc. 235 ft. over SE. slope.
30.80	Spur, slopes S.; desc. 35 ft. over SW. slope.
37.30	Ravine, drains S.; asc. 115 ft. over SE. slope.
40.88	<p>The $\frac{1}{4}$ sec. cor. of secs. 9 and 16, determined at record distance from the remains of the original bearing trees:</p> <p>A sawed fir stump, 18 ins. diam., bears East, 4 lks. dist., mkd. with a flat face and old axe marks on an opened blaze. (Record bearing, N. 80° E.)</p> <p>A sawed fir stump, 30 ins. diam., bears S. 5° E., 9 lks. dist., with no marks remaining. (Record bearing, South)</p> <p>At the corner point Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap marked</p> $\begin{array}{c} \frac{1}{4} \text{ S } 9 \\ \frac{1}{4} \text{ S } 16 \\ \text{T } 24 \text{ S } \text{ R } 6 \text{ W} \\ 1963 \end{array}$ <p>from which new bearing tree and bearing object:</p> <p>A sandstone outcropping, 7 x 6 x 4 ft. above ground, bears N. 37° W., 33 lks. dist., mkd. B X O.</p> <p>A sawed fir stump, 38 ins. diam., bears S. 69° W., 81 lks. dist., mkd. $\frac{1}{4}$ S16 BT.</p>
	N. 89° 12' W., beginning new measurement.
	Ascend 340 ft. over SE. slope, entering timber near ridge.
8.40	Ridge, summit of Yellow Creek Mtn., bears N. 30° E. and S. 30° W.; desc. 25 ft. over broken NW. slope, entering heavy timber and dense undergrowth.
12.60	Draw, drains NE.; asc. 30 ft. over NE. slope.
15.30	Leave timber, edge bears SE. and NW.; continue across logged and burned area, through light undergrowth.
16.40	Slope changes; asc. 10 ft. along S. slope.
24.50	Spur ridge bears N. 60° W. and S. 60° E.; desc. 210 ft.
37.35	Dirt road, 10 lks. wide, bears N. 40° W. and S. 40° E.
38.40	Draw, drains N. 40° W.; asc. 10 ft. over NE. slope.
39.65	The cor. of secs. 8, 9, 16, and 17. Land, mountainous. Soil, rocky clay loam.