

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of S. Bdy., T. 24 S., R. 8 W.

CHAINS	The cor. of secs. 33 and 34, only, on the S. bdy. of the Tp. monumented with an iron post $2\frac{1}{2}$ ins. diam., firmly set, with brass cap mkd. and witnessed as described in the official record.
	S. $89^{\circ} 32'$ W., on the S. bdy. of sec. 33, marking and blazing the true line.
	Descend 50 ft. over W. slope, through heavy timber and moderate undergrowth.
1.54	From this point the closing corner of secs. 3 and 4, T. 25 S., R. 8 W., bears South, 16 lks. dist., perpetuated by the Douglas County Surveyor, in 1958, with an iron post $1\frac{1}{2}$ ins. diam., firmly set, with brass cap mkd., and witnessed as described in the official record.
	Descend 85 ft. over W. slope.
2.80	Creek, 1 lk. wide, course N.; asc. 300 ft. over broken NE. slope.
9.60	Spur, slopes N.; desc. 20 ft. along broken N. slope.
16.50	Spur, slopes N. 30° W.; desc. 340 ft. along N. slope, changing to NW. slope.
32.25	Creek, 2 lks. wide, course N. 65° W.; asc. 30 ft. over NE. slope.
35.20	Spur, slopes N. 30° W.; desc. 80 ft. over NW. slope.
39.89	Point for the $\frac{1}{4}$ sec. cor. of sec. 33, only, at proportionate distance; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T 24 S R 8 W $\frac{1}{4}$ S 33 <hr style="width: 10%; margin: auto;"/> 1962
	from which
	A fir, 20 ins. diam., bears N. 50° E., 133 lks. dist., mkd. $\frac{1}{4}$ S 33 BT.
	A hemlock, 11 ins. diam., bears N. 56° W., 58 lks. dist., mkd. $\frac{1}{4}$ S 33 BT.
	The fork of a maple, 13 ins. diam., bears N. 9° W., 63 lks. dist., mkd. $\frac{1}{4}$ S 33 BT.
	Descend 35 ft. over SW. slope.
40.90	Creek, 2 lks. wide, course N. 30° W.; asc. 3 ft. over nearly level land.
43.60	Dry creek bed, 5 lks. wide, course N. 60° E.; asc. 710 ft. over steep E. slope.
57.45	Spur, ridge, bears N. 20° E. and S. 20° W.; desc. 285 ft. over broken W. slope.
73.00	Spring, drains NW.; desc. 140 ft. over broken NW. slope.
76.70	Creek, 1 lk. wide, course N. 70° W.; desc. 90 ft. over W. slope
80.48	The cor. of secs. 32 and 33, only, determined at record bearing and distance from the remaining original bearing trees: