

County Surveyor's Record, Douglas County, Oregon

CHAINS

Dependent Resurvey, Portion of S. Bdy., T. 24 S., R. 8 W

A fir, 60 ins. diam., bears S. 60° E., 31 lks.
dist., bark scribed T24S R8W S32 & 33 BT.

A fir, 48 ins. diam., bears N. 42° W., 91 lks.
dist., bark scribed T24S R W S32.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins.
in the ground, with brass cap marked

T 24 S | R 8 W

S 32 | S 33

S 4

T 25 S R 8 W

1962

from which new bearing trees

A hemlock, 24 ins. diam., bears N. 30° E., 149 lks.
dist., mkd. T24S R8W S33 BT.

A fir, 62 ins. diam., bears N. 16½° W., 133 lks.
dist., bark scribed T24S R8W S32 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, mayple, yew, and alder;
undergrowth; young timber, rhododendron, salal, vine
maple, huckleberry, salmonberry, fern, and arrowwood.

Dependent Resurvey of Portion of Subdivisional Lines,
T. 24 S., R. 8 W., Willamette Meridian, Oregon
(Restoring the 1894 survey by Henry L. Chandler)

From the cor. of secs. 27, 28, 33 and 34, monumented
with an iron post, 1½ ins. diam., firmly set, with brass
cap marked and witnessed as described in the official
record.

N. 0° 49' W., bet. secs. 27 and 28, marking and blazing
true line.

Ascend 355 ft. over SW. slope, through heavy old growth
timber and dense undergrowth.

18.30 Spur, slopes S. 80° W.; desc. 15 ft. over NW. slope,
changing to W. slope.

25.10 Bottom of descent, slopes S. 80° W.; asc. 10 ft. along
W. slope.

26.75 Top of ascent, slopes S. 75° W.; desc. 20 ft. along W.
slope.

31.50 Spur, slopes N. 60° W.; desc. 305 ft. over N. slope.

39.35 The ¼ sec. cor. of secs. 27 and 28 monumented with an
unmarked sandstone 12 x 8 x 4 ins. firmly set 8 ins.
in the ground, from which the remains of the original
NW. bearing tree.

A rotted fir snag, 28 ins. diam., bears N. 45° W.,
18 lks. dist., mkd. with old pitched face.
(Record, N. 55° W., 20 lks. dist.)