

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 24 S., R. 8 W.

CHAINS

A fir, 48 ins. diam., bears N. 66° W., 29 lks. dist., slope dist., 31 lks. mkd. with a healed blaze. (Record dist., 31 lks.) Reblaze and mark T24S R8W S16 BT.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap marked

T 24 S R 8 W
S 16 S 15
S 21 S 22
1962

from which a new bearing tree

A fir, 14 ins. diam., bears N. $33\frac{1}{2}^{\circ}$ W., 74 lks. dist., mkd. T24S R8W S15 BT.

Land, mountainous.

Soil, rocky clay.

Timber; fir, hemlock, madrone, maple, alder, dogwood, chinquapin and yew; undergrowth; young timber, salal, rhododendron, poison oak, hazel, huckleberry, fern, salmonberry, vine maple, arrowwood, Oregon grape and thimbleberry.

From the cor. of secs. 32 and 33, only, on the S. bdy. of the Tp.

N. 1° 59' E., bet. secs. 32 and 33.

Descend 15 ft. along W. slope, through heavy timber and moderate undergrowth.

0.95 Case Knife Creek, 3 lks. wide, course N. 10° E., desc. 85 ft. along E. slope, changing to NE. slope.

9.20 Creek, 4 lks. wide, course N. 70° E.; asc. 105 ft. along broken E. slope.

18.60 Spur, slopes E.; desc. 195 ft. over broken NE. slope.

25.50 Dry creek bed, 4 lks. wide, course E.; asc. 450 ft. over SE. slope.

39.50 Spur ridge, bears N. 70° E. and S. 70° W.

39.54 Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33, proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap marked

S 32 S 33
T 24 S R 8 W
1962

from which

A fir, 52 ins. diam., bears S. $87\frac{1}{2}^{\circ}$ E., 56 lks. dist., mkd. $\frac{1}{4}$ S33 BT.

A fir, 38 ins. diam., bears N. 30° W., 37 lks. dist., mkd. $\frac{1}{4}$ S32 BT.

*FD. OK 11/83
BY H. Johnson
M 95-41*