

County Surveyor's Record, Douglas County, Oregon

CHAINS

Dependent Resurvey, Subdivisional Lines, T. 24 S., R. 8 W.

A fir, 34 ins. diam., bears S. 56° W., 98 lks.
dist., mkd. with a healed blaze and old axe marks.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins.
in the ground, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ \text{S } 29 \mid \text{S } 28 \\ \text{T } 24 \text{ S } \mid \text{R } 8 \text{ W} \\ 1962 \end{array}$$

from which new bearing trees

A cedar, 13 ins. diam., bears S. 27° E., 53 lks.
dist., mkd. $\frac{1}{4}$ S28 BT.

A fir, 10 ins. diam., bears S. 81° W., 36 lks.
dist., mkd. $\frac{1}{4}$ S29 BT.

N. 0° 20' W., beginning new measurement.

Ascend 240 ft. over S. slope, through heavy timber and
moderate undergrowth.

11.70 Spur ridge, bears N. 70° E. and S. 70° W.; desc. 530 ft.
over broken N. slope.

30.20 Miner Creek, 10 lks. wide, course E.; asc. 180 ft. over
S. slope.

40.16 The cor. of secs. 20, 21, 28 and 29, determined at
record bearing and distance from the original bearing
trees:

A fir, 30 ins. diam., bears N. 40° E., 84 lks.
dist., mkd. with a healed blaze and cruiser.
marks. Reblaze and mark T24S R8W S21 BT.

A fir, 20 ins. diam., bears S. $22\frac{1}{4}^{\circ}$ E., 19 lks.
dist., mkd. with a healed blaze and cruiser
marks. Reblaze and mark T24S R8W S28 BT.

A fir, 27 ins. diam., bears S. 35° W., 50 lks.
dist., mkd. with a healed blaze and old axe
marks. Reblaze and mark T24S R8W S29 BT.

A fir, 32 ins. diam., bears N. $5\frac{1}{2}^{\circ}$ W., 38 lks.
dist., mkd. with old axe marks, a healed blaze,
and cruiser marks. Reblaze and mark T24S R8W
S20 BT.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins.
in the ground, with brass cap marked

$$\begin{array}{c} \text{T } 24 \text{ S } \text{R } 8 \text{ W} \\ \text{S } 20 \mid \text{S } 21 \\ \text{S } 29 \mid \text{S } 28 \\ 1962 \end{array}$$