

County Surveyor's Record, Douglas County, Oregon

Resurvey, Portion of Subdivisional Lines, T. 25 S., R. 2 W.

CHAINS

- 15.33 Top of ascent; desc. 14 ft. over SW. slope.
- 17.35 Branch, 2 lks. wide, course S. 55° E.; asc. 74 ft. over NE. slope.
- 20.42 Spur, slopes N. 30° E.; desc. 13 ft. along N. slope.
- 21.42 Branch, 1 lk. wide, course N. 30° E.; asc. 602 ft. over SE. slope.
- 36.67 Spur, slopes N. 70° E.; thence along N. slope.
- 40.51 The cor. of secs. 2, 3, 10, and 11, determined at record distance from the remaining original bearing trees:

A hemlock, 12 ins. diam., bears N. 51½° E., 33 lks. dist., blaze healed. (Record bearing, N. 51° E.) The blaze has been chopped out showing scribe marks 2R 5W S2.

A chinquapin, 5 ins. diam., bears S. 47½° E., 28 lks. dist., blaze rotted, partial scribe marks visible. (Record bearing, S. 47° E.)

A fir, 36 ins. diam., bears N. 57° W., 61 lks. dist., blaze healed. (Record: bears N. 56° W., 59 lks. dist.)

At the corner point

Set an iron post, 36 ins. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

*FD. OK 2/92
G. LANG M114-57*

T 25 S	R 2 W
S 3	S 2
S 10	S 11

1951

from which

A hemlock, 14 ins. diam., bears N. 64° E., 33 lks. dist., mkd. T25S R2W S2 BT.

A hemlock, 10 ins. diam., bears S. 35½° E., 32 lks. dist., mkd. T25S R2W S11 BT.

A hemlock, 12 ins. diam., bears S. 51½° W., 120 lks. dist., mkd. T25S R2W S10 BT.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, sugar pine, yew, madrone, chinquapin, and dogwood; undergrowth, vine maple, salal, huckleberry, Oregon grape, and rhododendron.

N. 0° 03' E., bet. secs. 2 and 3.

Descend 395 ft. over N. slope, through heavy timber and dense undergrowth.

- 10.49 Branch, 4 lks. wide, course N. 80° E.; asc. 322 ft. over S. slope.

- 21.52 Spur, slopes N. 85° E., desc. 284 ft. over NE. slope.