

County Surveyor's Record, Douglas County, Oregon

Resurvey, Portion of Subdivisional Lines, T. 25 S., R. 2 W.

CHAINS	
40.21	<p>The $\frac{1}{4}$ sec. cor. of secs. 2 and 3, monumented with a basalt stone, 12 x 10 x 8 ins., firmly set, marked $\frac{1}{4}$ on W. face, from which the original bearing trees:</p> <p style="margin-left: 40px;">A cedar, 18 ins. diam., bears N. $81\frac{1}{4}^{\circ}$ E., 14 lks. dist., blaze rotted, scribe marks $\frac{1}{4}$ 2 visible. (Record: bears N. 81° E., 12 lks. dist.)</p> <p style="margin-left: 40px;">A dogwood, 7 ins. diam., bears S. 34° W., 14 lks. dist., blaze rotted. (Record: bears S. 36° W., 15 lks. dist.)</p> <p>At the corner point</p> <p>Set an iron post, 36 ins. long, 1 inch diam., 28 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> $\begin{array}{c} \frac{1}{4} \\ \\ \text{S } 3 \text{S } 2 \\ \\ 1951 \end{array}$ </div> <p>from which</p> <p style="margin-left: 40px;">A hemlock, 24 ins. diam., bears N. 63° E., 23 lks. dist., mkd. $\frac{1}{4}$ S2 BT.</p> <p style="margin-left: 40px;">A hemlock, 12 ins. diam., bears S. 55° 45' W., 60 lks. dist., mkd. $\frac{1}{4}$ S3 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 28' W., beginning new measurement.</p> <p>Descend 245 ft. over NE. slope.</p>
9.80	Creek, 15 lks. wide, course S. 55° E.; asc. 40 ft. over S. slope.
12.00	Blazed trail, bears N. 40° W. and S. 40° E.; asc. 225 ft. over S. slope.
18.00	Spur, slopes S. 30° W., from N.; asc. 200 ft. along spur.
25.80	Leave spur; asc. 170 ft. over SW. slope.
35.35	<p>Corner of Parcels 38 and 40, sec. 2, as shown in Court Decree "Civil No. 60-135, Oregon". The corner is monumented with an iron pipe, 25 ins. long, $\frac{3}{4}$ ins. diam., firmly driven 20 ins. in the ground, from which</p> <p style="margin-left: 40px;">A fir, 12 ins. diam., bears N. $56\frac{3}{4}^{\circ}$ E., 20 lks dist., marked P38 S2 BT.</p> <p style="margin-left: 40px;">A hemlock, 17 ins. diam., bears S. 27° E., 77 lks. dist., marked P40 S2 BT.</p> <p>Ascend 95 ft. over broken SW. slope</p>
45.40	Small spur, slopes S. 70° W.; desc. slightly over NW. slope
46.40	Draw, drains S. 40° W.; asc. 235 ft. over SW. slope, changing to SE. slope.
53.10	Spur, slopes N. 85° E.; desc. 470 ft. over NE. slope.