

County Surveyor's Record, Douglas County, Oregon

Resurvey, Portion of Subdivisional Lines, T. 25 S., R. 2 W.

CHAINS

N. $0^{\circ} 22'$ W., bet. secs. 3 and 4.

Descend 7 ft. over NE. slope, through heavy timber and dense undergrowth.

0.66 Branch, dry, course S. 80° E.; asc. 163 ft. over SE. slope.5.03 Spur, slopes S. 70° E.; desc. 107 ft. over E. slope.15.24 Branch, 2 lks. wide, dry, course S. 50° E.; asc. 304 ft. over SW. slope.

21.10 Slope changes; asc. 531 ft. over S. slope.

34.83 Spur, slopes E.; desc. 92 ft. over N. slope.

39.42 The $\frac{1}{4}$ sec. cor. of secs. 3 and 4, monumented with a basalt stone, 14 x 10 x 4 ins., firmly set, marked $\frac{1}{4}$ on W. face, from which the original bearing trees:A hemlock, 26 ins. diam., bears N. 42° W., 3 lks. dist., blaze healed. (Record distance, 2 lks.)A hemlock, 8 ins. diam., bears S. 56° E., 24 lks. dist., blaze chopped open, scribe marks S3 visible. (Record bearing, S. 43° E.)

At the corner point

Set an iron post, 36 ins. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} \frac{1}{4} \\ S\ 4\ | \ S\ 3 \\ 1951 \end{array}$$

from which

A hemlock, 38 ins. diam., bears S. 47° E., 43 lks. dist., mkd. $\frac{1}{4}$ S3 BT.

Bury the original corner stone alongside the iron post.

N. $5^{\circ} 50'$ E., beginning new measurement.

Descend 50 ft. over steep NE. slope.

0.95 NW. base of a bluff, 30 ft. high; desc. 350 ft. over NE. slope.

11.70 Spur, slopes N. 25° E.; desc. 545 ft. over NW. slope.26.97 Corner of Parcels 41 and 42, sec. 4, as shown in Court Decree "Civil No. 60-135, Oregon". The corner is monumented with an iron pipe, 24 ins. long, $\frac{3}{4}$ in. diam., firmly driven 20 ins. in the ground, from whichA fir, 8 ins. diam., bears S. $61\frac{1}{4}^{\circ}$ W., 46 lks. dist., marked P42 S4 BT.A fir, 9 ins. diam., bears N. $4\ \frac{3}{4}^{\circ}$ W., 69 lks. dist., marked P41 S4 BT.

Descend 220 ft. over NW. slope.