

County Surveyor's Record, Douglas County, Oregon

Resurvey, Portion of Subdivisional Lines, T. 25 S., R. 2 W.

CHAINS

$$\frac{1}{4} \frac{S \ 4}{S \ 9}$$

1951

from which

A sugar pine, 7 ins. diam., bears N. $4\frac{1}{2}^{\circ}$ W., 8 lks. dist., mkd. $\frac{1}{4}$ S4 BT.

A sugar pine, 14 ins. diam., bears S. 38° E., 35 lks. dist., mkd. $\frac{1}{4}$ S9 BT.

Bury the original corner stone alongside the iron post.

N. $88^{\circ} 19'$ W., beginning new measurement.

Descend 461 ft. over SW. slope.

20.19 Point of spur, slopes W., desc. 461 ft. over W. slope.

30.85 Branch, 3 lks. wide, course N. 50° W., desc. 10 ft. over NW. slope.

33.00 Branch, 4 lks. wide, course S. 80° W., desc. 34 ft. along S. slope.

39.10 The cor. of secs. 4, 5, 8, and 9, determined at record distance from the original NE. and NW. bearing trees:

A cedar, 30 ins. diam., bears N. $59\frac{1}{2}^{\circ}$ E., 37 lks. dist., blaze partially healed, partial scribe marks visible. (Record bearing, N. 54° E.)

A maple, 10 ins. diam., bears N. $83\frac{1}{2}^{\circ}$ W., 11 lks. dist., blaze rotted. (Record bearing, N. 63° W.)

At the corner point

Set an iron post, 36 ins. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T 25 S R 2 W

$$\frac{S \ 5 | S \ 4}{S \ 8 | S \ 9}$$

1951

from which

A hemlock, 10 ins. diam., bears N. $20\frac{1}{2}^{\circ}$ W., 38 lks. dist., mkd. T25S R2W S5 BT.

A cedar, 30 ins. diam., bears S. 11° E., 36 lks. dist., mkd. T25S R2W S9 BT.

A cedar, 12 ins. diam., bears S. $20\frac{1}{2}^{\circ}$ W., 43 lks. dist., mkd. T25S R2W S8 BT.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, sugar pine, cedar, maple, yew, madrone, dogwood, and chinquapin, undergrowth, vine maple, salal, huckleberry, Oregon grape, and rhododendron.