

## County Surveyor's Record, Douglas County, Oregon

Resurvey, Portion of Subdivisional Lines, T. 25 S., R. 2 W.

CHAINS

Bury the original corner stone alongside the iron post.

N.  $89^{\circ} 09'$  W., beginning new measurement.

Ascend 368 ft. over NE. slope.

9.90 Spur, slopes S.  $50^{\circ}$  E.; desc. 329 ft. along S. slope changing to SW. slope.

35.32 Branch, 1 lk. wide, course S.  $10^{\circ}$  E.; asc. 109 ft. over E. slope changing to S.

40.22 The cor. of secs. 5, 6, 7, 8, monumented with a basalt stone, 16 x 8 x 4 ins., firmly set, marked with 5 notches on the S. and E. edges, from which the original bearing trees:

A yew, 12 ins. diam., bears N.  $52^{\circ} 45'$  E., 65 lks. dist., partial scribe marks visible. (Record bearing, N.  $51^{\circ}$  E.)

A fir, 24 ins. diam., bears S.  $34\frac{1}{2}^{\circ}$  E., 11 lks. dist., blaze healed. (Record bearing, S.  $34^{\circ}$  E.)

A yew, 14 ins. diam., bears S.  $56^{\circ}$  W., 70 lks. dist., partial scribe marks visible. (Record: bears S.  $59^{\circ}$  W., 73 lks. dist.)

A yew, 14 ins. diam., bears N.  $77^{\circ} 45'$  W., 59 lks. dist., blaze rotted, partial scribe marks visible. (Record: bears N.  $77^{\circ}$  W., 61 lks. dist.)

At the corner point

Set an iron post, 36 ins. long, 2 ins. in diam., 28 ins. in the ground, with brass cap mkd.

T	25	S	R	2	W
	S	6	S	5	
	S	7	S	8	
					1951

from which

A fir, 50 ins. diam., bears N.  $86\frac{1}{2}^{\circ}$  W., 76 lks. dist., mkd. T25S R2 W S6 BT.

A fir, 48 ins. diam., bears N.  $31^{\circ} 45'$  E., 45 lks. dist., mkd. T25S R2W S5 BT.

Bury the original corner stone alongside the iron post.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, sugar pine, cedar, maple, yew, madrone, dogwood, and chinquapin; undergrowth, vine maple, salal, huckleberry, Oregon grape, and rhododendron.

S.  $88^{\circ} 34'$  W., bet. secs. 6 and 7.

Asc. 16 ft. over S. slope, through heavy timber and dense undergrowth.