

County Surveyor's Record, Douglas County, Oregon

Resurvey, Portion of Subdivisional Lines. T. 25 S., R. 2 W.

CHAINS

- 5.27 Ravine, course S.; asc. 861 ft. over rocky SE. slope.
- 36.47 Branch, 4 lks. wide, course SE.; asc. 111 ft. over NE. slope.
- 39.28 The $\frac{1}{4}$ sec. cor. of secs. 6 and 7, monumented with a basalt stone, 16 x 8 x 6 ins., firmly set, marked $\frac{1}{4}$ on N. face, from which the original bearing trees:
- A fallen fir, 50 ins. diam., bears N. 17° E., 32 lks. dist., blaze healed.
- A hemlock, 18 ins. diam., bears S. $31^{\circ} 45'$ E., 59 lks. dist., partially healed blaze, scribe marks $\frac{1}{4}$ S7 BT. visible. (Record bearing, S. 29° E.)
- At the corner point
- Set an iron post, 36 ins. long, 1 in. diam., 28 ins. in the ground, with brass cap mkd.
- $\frac{1}{4}$ $\frac{S}{S}$ $\frac{6}{7}$
- 1951
- from which
- A hemlock, 10 ins. diam., bears N. $46\frac{1}{4}^{\circ}$ E., 61 lks. dist., mkd. $\frac{1}{4}$ S6 BT.
- Bury the original corner stone alongside the iron post.
-
- S. $83^{\circ} 34'$ W., beginning new measurement.
- Asc. 463 ft. over rocky NE. slope.
- 14.60 Spur, slopes N.; desc. 3 ft. over NW. slope.
- 15.56 Spring branch, 1 lk. wide, course NE.; asc. 179 ft. over SE. slope.
- 28.39 The closing cor. of sec. 6 and 7, on the W. bdy. of the Tp., described in the field notes of the 1943 dependent resurvey of the E. bdy. of T. 25 S., R. 3 W.
- Land, mountainous.
Soil, rocky clay loam.
Timber, fir, hemlock, sugar pine, cedar, maple, yew, madrone, dogwood, and chinquapin; undergrowth, vine maple, salal, huckleberry, Oregon grape, and rhododendron.
-
- From the cor. of secs. 5, 6, 7, and 8.
- N. $0^{\circ} 35'$ E., bet. secs. 5 and 6.
- Asc. 136 ft. over S. slope, through heavy timber and dense undergrowth.
- 6.47 Top of ascent; desc. 12 ft. along E. slope.
- 7.14 Branch, 2 lks. wide, course SE., asc. 491 ft. over S. slope.
- 10.25 Rock bluff, 30 ft. high, bears N. 25° W. and S. 25° E.