

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 25 S., R. 5 W.

CHAINS

Descend 35 ft. over N. slope, through medium timber and dense undergrowth, blazing the true line.

62.20 Draw, drains W.; asc. 55 ft. over S. slope.

67.15 Spur, slopes W.; desc. 555 ft. over N. slope.

79.04 The cor. of secs. 25, 26, 35, and 36, occupied by the original corner tree, a fir, 33 ins. diam., mkd. T25S R5W S3 on opened blaze on S. side of tree, and with healed blazes on E., W. and N. sides of tree, from which bearing trees marked by Milo Godfrey, Deputy County Surveyor, in 1962:

A fir, 17 ins. diam., bears S. $2\frac{1}{2}^{\circ}$ E., 31 lks. dist., mkd. T25S R5W WC S36 CS BT, on open blaze.

A fir, 27 ins. diam., bears S. $38\frac{3}{4}^{\circ}$ W., 40 lks. dist., mkd. T25S R5W WC S35 CS BT, on open blaze.

A hemlock, 9 ins. diam., bears N. $28\frac{1}{2}^{\circ}$ W., 54 lks. dist., mkd. T25S R5W WC S26 CS BT, on double blaze.

and a new bearing tree,

A hemlock, 8 ins. diam., bears N. 61° E., 31 lks. dist., mkd. T25S R5W S25 BT.

From this point, a reference monument established by Godfrey, an iron post, 36 ins. long, 1 in. diam., protruding 8 ins. above ground, firmly set, bears South, 18 lks. dist., with brass cap marked, County Surveyor's Office, T25S S26 W C S35 R5W 12 FT N. TO COR. 1962.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, oak, hemlock, madrone, yew, alder, and cedar; undergrowth, young timber, hazel, arrowwood, ceanothus, salal, Oregon grape, huckleberry, vines, ferns, and grasses.

From the cor. of secs. 2, 3, 34, and 35, on the S. bdy. of the Tp.

N. 0° $42'$ E., bet. secs. 34 and 35.

Descend 120 ft. over broken NW. slope, through widely scattering timber and light undergrowth, through a recent burn.

9.50 Enter open draw, edge bears NE. and S. 10° W.; desc. 20 ft. over swamp and draw.

12.20 Center of draw, drains N. 10° E.; desc. 20 ft. across swamp.

24.60 Graded and graveled road, 20 lks. wide, with buried telephone cable along S. side of road, bears N. 10° E. and SW.; asc. 60 ft. over SE. slope.

36.50 Point of a spur, slopes E.; desc. 15 ft. over NE. slope.

38.90 Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.