

## County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 25 S., R. 5 W.

CHAINS	
	From the cor. of secs. 25, 26, 35, and 36. S. 89° 05' W., bet. secs. 26 and 35. Ascend 40 ft. over NE. slope, through heavy timber and dense undergrowth.
1.90	Top of ascent, slopes N.; desc. 80 ft. over W. slope.
4.70	Ravine, drains N.; asc. 35 ft. along broken N. slope.
15.40	Spur, slopes NW.; desc. 140 ft. over W. slope.
18.15	Creek, 3 lks. wide, course N.; asc. 405 ft. over E. slope.
26.80	Spur ridge, bears N. 10° W. and S. 10° E.; desc. 490 ft. over SW. slope.
39.89	The $\frac{1}{4}$ sec. cor. of secs. 26 and 35, reestablished by G. Robert Lecklider, Registered Land Surveyor, in 1961, and recorded with the Douglas County Surveyor. Lecklider states that he reestablished the corner at midpoint and on line between section corners. The corner was remonumented by Milo Godfrey, Deputy County Surveyor, in 1962, with an iron post, 36 ins. long 1 in. diam., protruding 12 ins. above ground, firmly set, with brass cap marked  <div style="text-align: center;">           T 25 S  <math>\frac{1}{4}</math> <math>\frac{S\ 26}{S\ 35}</math>            R 5 W            1962         </div> from which trees marked by Lecklider, in 1961: A fir, 22 ins. diam., bears S. 29 $\frac{1}{2}$ ° E., 122 lks. dist., mkd. $\frac{1}{4}$ S35 BT, on double blaze. A fir, 10 ins. diam., bears S. 30° W., 94 lks. dist., mkd. $\frac{1}{4}$ S35 BT, on double blaze. and a new bearing tree: A sawed fir stump, 24 ins. diam., bears N. 63 $\frac{3}{4}$ ° E., 86 lks. dist., mkd. $\frac{1}{4}$ S26 BT.  <hr style="width: 20%; margin: auto;"/> S. 89° 03' W., beginning new measurement. Descend 2 ft. over SW. slope, through scattering timber and moderate undergrowth.
0.55	Creek, 2 lks. wide, course N. 30° W.; desc. 5 ft. over bottom land.
0.95	Graded and graveled road, 20 lks. wide, bears N. 20° E., curving to N., and S. 30° W.; desc. 15 ft. over bottom land.
2.32	Telephone cable, buried, bears N. 30° E. and S. 30° W.
4.15	Cooper Creek, 10 lks. wide, course N. 20° E.; continue over level creek bottom.
5.10	Edge of bottom, bears N. 20° E. and S. 30° W.; asc. 580 ft. over broken SE. slope, changing to E. slope.