

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Subdivisional Lines, T. 25 S., R. 5 W.

CHAINS

- 22.50 Spur, slopes SE.; asc. 200 ft. over SE. slope.
- 33.50 Spur, slopes S., curving to SE.; asc. 45 ft. over SE. slope.
- 39.54 The cor. of secs. 26, 27, 34 and 35.

Land, mountainous.

Soil, clay loam.

Timber, fir, pine, hemlock, cedar, madrone, yew, and alder; undergrowth, young timber, hazel, huckleberry, salal, arrowwood, ceanothus, Oregon grape, vines, ferns, and grass.

Subdivision of Section 35, T. 25 S., R. 5 W.

The following subdivision of section 35 was executed in conformity with legal surveying practice. The record of true line notes, only, is set forth in the following field notes.

From the $\frac{1}{4}$ sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp.

N. $0^{\circ} 19'$ E., on the N. and S. center line of sec. 35.

Ascend 260 ft. over SE. slope, through scattering timber and light undergrowth, along a new wire fence.

- 11.40 Ridge, bears N. 80° E. and S. 80° W.; desc. 610 ft. over N. slope.

- 39.32 Point for the center $\frac{1}{4}$ sec. cor. of sec. 35, at intersection with the E. and W. center line.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap marked

C $\frac{1}{4}$ S 35
1963

from which

A fir, 14 in. diam., bears S. 71° E., 98 lks. dist., mkd. C $\frac{1}{4}$ S35 BT.

A fir, 20 ins. diam., bears N. 74° W.; 41 lks. dist., mkd. C $\frac{1}{4}$ S35 BT.

The corner is located in the N. and S. fence line.

Descend 15 ft. over N. slope in a draw.

- 41.10 Dirt road, 10 lks. wide, bears E. and W.
- 41.60 Creek, 4 lks. wide, course W.; continue over level creek bottom.
- 42.60 Leave bottom, bears E. and W.; asc. 70 ft. over S. slope.
- 45.35 Spur, slopes W.; asc. 230 ft. over S. slope.
- 49.60 Dirt road, 20 lks. wide, bears E. and W.
- 56.30 Fence corner from which fences extend E. and S., only.